

Scheda tecnica/Data Sheet: 73107



DESCRIZIONE PRODOTTO / PRODUCT DESCRIPTION

Lng.	Descrizione / Description
IT	Adattatore industriale spina 2P+T 16A 200-250V 6h IP44 1 presa 2P+T 16A 200-250V 6h IP44 1 presa bipasso italo/Schuko 2P+T 16A IP44
EN	Adaptor for industrial purposes plug 2P+E 16A 200-250V 6h IP44 1 socket 2P+E 16A 200-250V 6h IP44 1 socket italian 10-16A/Schuko std. 2P+E 16A IP44

CARATTERISTICHE PRINCIPALI / FEATURES

Lng.	Caratteristica / Feature	Valore / Value
IT	Numero prese/uscite	2
IT	Tipo prese	2P+T 16A 230V 6h IP44
IT	Tipo prese	Bipasso IT/DE 2P+T 16A IP44
IT	Tipo spina	2P+T 16A 230V 6h IP44
IT	Protezione IP	IP20
IT	Colore	Blu
IT	Confezione singola	-
IT	Marchi qualità	CE
IT	Tensione nominale (Volt)	200-250 V AC

Lng.	Caratteristica / Feature	Valore / Value
IT	Classificazione ELECTROCOD	22.0.1
EN	Number sockets/outlets	2
EN	Sockets type	2P+E 16A 230V 6h IP44
EN	Sockets type	Dual-size IT/DE 2P+E 16A IP44
EN	Plug type	2P+E 16A 230V 6h IP44
EN	Ingress protection	IP20
EN	Colour	Blue
EN	Single packaging	-
EN	Quality marks	CE
EN	Nominal voltage (Volt)	200-250 V AC
EN	ELECTROCOD classification	22.0.1

CARATTERISTICHE ETIM / ETIM FEATURES

Lng.	Caratteristica / Feature	Um	Valore / Value
IT	Tipologia		set
IT	Con spina per AUS (AS/NZS 3112) (tipo I)		No
IT	Con spina per BE/DE/NL/RU (contatto di protezione, tipo F)		No
IT	Con spina per BE / DE / NL / RU / CH (Euro) (tipo C)		No
IT	Con spina per CH (SEV 1011 tipo 11) (tipo J)		No
IT	Con spina per CH (SEV 1011 tipo 12) (tipo J)		No
IT	Con spina per CH (SEV 1011 tipo 23) (tipo J)		No
IT	Con spina per FR (pin di terra) (tipo E)		No
IT	Con spina per UK/HK (BS 1363) (tipo G)		No
IT	Con spina per IT (S/P 11)		No
IT	Con spina per IT (S/P 17) (tipo L)		No
IT	Con spina per USA/CA/CN (NEMA 1-15) (tipo A)		No
IT	Con spina per USA/CA/CN (NEMA 5-15) (tipo B)		No
IT	Tipo di presa		Altro
IT	Numero di porte USB		0
IT	Colore		grigio
IT	Tensione nominale	V	Da 200 a 250
IT	Corrente nominale	A	Da 0 a 0
EN	Model		Set
EN	With plug for AU/NZ/PG/AR (AS/NZS 3112) (type I)		No
EN	With plug for BE/DE/NL/RU (protective contact CEE 7/4, type F)		No
EN	With plug for BE/DE/NL/RU/CH (Euro) (type C)		No
EN	With plug for CH (SEV 1011 type 11) (type J)		No
EN	With plug for CH (SEV 1011 type 12) (type J)		No
EN	With plug for CH (SEV 1011 type 23) (type J)		No
EN	With plug for FR (earth pin) (type E)		No
EN	With plug for UK/HK (BS 1363) (type G)		No
EN	With plug for IT (S/P 11)		No
EN	With plug for IT (S/P 17) (type L)		No
EN	With plug for US/CA/CN (NEMA 1-15) (type A)		No
EN	With plug for US/CA/CN (NEMA 5-15) (type B)		No
EN	Type of bus		Other

Lng.	Caratteristica / Feature	Um	Valore / Value
EN	Number of USB ports		0
EN	Colour		Grey
EN	Nominal voltage	V	From 200 to 250
EN	Nominal current	A	From 0 to 0

Fanton spa si riserva di apportare modifiche e migliorie al prodotto in qualsiasi momento e senza alcun preavviso
Fanton spa reserves the right to change and update the product at any time and without warning.

Date: 08/05/2025 Revision: 0