


Start Surface Slim IP54 - Square Sensor

START SURFACE SLIM IP54 SQUARE 1900LM 2CCT MW WH

0043520



Caratteristiche prodotto

- Ceiling / wall round luminaire with integrated LED. Perfect solution for corridors, circulation areas or bathrooms. Even and uniform light in a slim but robust design. Power 18 W, lumen output 1900 lumens, lumen efficacy 105 lm/W, dual color temperature (3000K/4000K). Supplied with non dimmable driver and built-in motion sensor. Default settings as Stand-by time 0s, Stand-by dim level 15%, Daylight 10lux, Hold-time 60s, Sensitivity 100%. Mains Voltage 220-240V~. Body Size: 280mm square x 53mm height. IK07, IP54 Protection rating. PC Polycarbonate Opal diffuser. Low maintenance with 65000 hours LED lifespan expectancy. Warranty: 3 years.



PANORAMICA DEL PRODOTTO

Nome prodotto	START SURFACE SLIM IP54 SQUARE 1900LM 2CCT MW WH
Tecnologia	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Montaggio	Ceiling surface mounting, Wall surface mounted
General application	Strutture alberghiere
ETIM Class	EC002892
E-number Finlandia	4278451
Garanzia	3 years
Fixture luminous flux (lm)	1900
Luminaire efficacy (lm/W)	105
Colore della luce	Neutral White
CRI (Ra)	80
Consistenza colore (SDCM)	SDCM4
Beam Angle (°)	120
Gruppo di rischio fotobiologico	RG0
Potenza totale (W)	18
Electrical protection	Classe II
Tipologia reattore	LED driver constant current
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Colore corpo lampada	Bianco
IP rating	IP54
IK rating	IK07
Product EAN number	5410288435206
Dimming method	N/A

TABELLA DATI

Dati generali

Nome prodotto	START SURFACE SLIM IP54 SQUARE 1900LM 2CCT MW WH
Tecnologia	LED

Start Surface Slim IP54 - Square Sensor

START SURFACE SLIM IP54 SQUARE 1900LM 2CCT MW WH
0043520

Cap/Base	N/A
Housing	PC Polycarbonate
Montaggio	Ceiling surface mounting, Wall surface mounted
General application	Strutture alberghiere
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
E-number Finlandia	4278451
Garanzia	3 years

Dati ottici

Fixture luminous flux (lm)	1900
Luminaire efficacy (lm/W)	105
Correlated colour temperature range (K)	3000 - 4000
Colore della luce	Neutral White
CRI (Ra)	80
Consistenza colore (SDCM)	SDCM4
Beam Angle (°)	120
Distribution type	Diffuse
Gruppo di rischio fotobiologico	RG0

Dati elettrici

Potenza totale (W)	18
Tensione di rete (V)	220-240V
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	18
Electrical protection	Classe II
Control gear required	No
Tipologia reattore	LED driver constant current
Transformer required	No
Dimmable	No
Drive current (mA)	480
Corrente di spunto (A)	4.5
Durata picco di corrente (µs)	100
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Quantità max. apparecchi per interruttore 16A tipo C	50
Max. Luminaires per 16A B Breaker	32

Dati vita utile

Vita utile nominale - L70 B50	65000
Vita utile nominale - L80 B50	42000
Vita utile nominale - L90 B50	21000

Start Surface Slim IP54 - Square Sensor

START SURFACE SLIM IP54 SQUARE 1900LM 2CCT MW WH
0043520

Dati dimensionali

Colore corpo lampada	Bianco
IP rating	IP54
IK rating	IK07
Diffuser finish	Opalino
Diffuser material	PC Polycarbonate
Nominal Product Height (mm)	53
Nominal Product Diameter (mm)	280
Peso (Kg)	1.157

Dati di imballo

Tipologia imballo singolo	Carton
Product EAN number	5410288435206
Lunghezza imballo singolo (mm)	28.5
Larghezza imballo singolo (cm)	5.8
Packaging single depth (cm)	28.7
DUN14 (outer)	15410288435203
Quantità per imballo esterno	6
Packaging outer length / height (cm)	37.5
Packaging outer width (cm)	30.0
Packaging outer depth (cm)	30.5

Dati di sicurezza

Temperatura ottimale di utilizzo (°C)	-20-40
---------------------------------------	--------

FOTOMETRIA

