


PIR Detectors - Ceiling-mounted

Compact PIR presence/absence detector with lux level sensing. time delay function and infrared override

0041540



Caratteristiche prodotto

- PIR sensor with switching capability. On/off switching via lux sensing. Dual sensitivity. Absence/presence detection. Adjustable time delay (10sec to 99min). Up to 7m detection radius at 2.8m mounting height. Programmable via handset. Mounting accessories available. Can be connected in parallel for larger areas and L-shaped corridors. Up to 10A load.



PANORAMICA DEL PRODOTTO

Nome prodotto	Compact PIR presence/absence detector with lux level sensing. time delay function and infrared override
Tecnologia	Controls
Montaggio	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Istruzione, Strutture alberghiere, Logistics & Industry, Musei e gallerie, Uffici, Esercizi commerciali, Residential & Consumer
ETIM Class	EC000533
Carico massimo (A)	10
Input	PIR, IR, Lux
Input protocol	PIR Sensor, IR Signal, Lux sensor
Protocollo in uscita	Switched
Numero di canali	1
IP rating	IP40
Product EAN number	5410288415406

TABELLA DATI

Dati generali

Nome prodotto	Compact PIR presence/absence detector with lux level sensing. time delay function and infrared override
Configurato senza PC	Yes
Tecnologia	Controls
Montaggio	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Istruzione, Strutture alberghiere, Logistics & Industry, Musei e gallerie, Uffici, Esercizi commerciali, Residential & Consumer
Operating temperature range (°C)	-10°C...+35°C
ETIM Class	EC000533

Dati elettrici

Carico massimo (A)	10
Input	PIR, IR, Lux
Input protocol	PIR Sensor, IR Signal, Lux sensor

PIR Detectors - Ceiling-mounted

Compact PIR presence/absence detector with lux level sensing. time delay function and infrared override

0041540

Protocollo in uscita	Switched
Numero di canali	1
Tensione di rete (V)	220-240V
Frequenza di rete (HZ)	50

Dati dimensionali

IP rating	IP40
Lunghezza nominale del prodotto (mm)	76
Larghezza nominale prodotto (mm)	76
Nominal Product Height (mm)	68.5
Cutout Dimensions (W x L in mm or Diameter in mm)	64
Peso (Kg)	0.105
Recessed Depth (mm)	65

Dati di imballo

Tipologia imballo singolo	Carton
Product EAN number	5410288415406
Lunghezza imballo singolo (mm)	9.5
Larghezza imballo singolo (cm)	9.5
Packaging single depth (cm)	7.5
Quantità per imballo esterno	100
Packaging outer length / height (cm)	47.0
Packaging outer width (cm)	47.0
Packaging outer depth (cm)	52.0

Dati di sicurezza

Temperatura ottimale di utilizzo (°C)	-10-35
---------------------------------------	--------

DISEGNI TECNICI

