

## Microwave detectors - Ceiling-mounted and tilt adjustable

*Ceiling mounted MW detector 10m range. Lux level sensing & time delay function (Z1)*

0041548



### Caratteristiche prodotto

- Ceiling mounted microwave presence detector. 10m detection range. Lux-level sensing. Dual sensitivity configurable ON and OFF motion sensitivity. Self contained unit. No external control boxes saves time on installation. Made from robust materials. Programmable using programming handsets. IP40. Region 1 configuration UK



## PANORAMICA DEL PRODOTTO

|                      |                                                                                                                                 |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Nome prodotto        | Ceiling mounted MW detector 10m range. Lux level sensing & time delay function (Z1)                                             |
| Tecnologia           | Controls                                                                                                                        |
| Montaggio            | Ceiling recessed mounting                                                                                                       |
| Environment          | Interior                                                                                                                        |
| General application  | Istruzione, Strutture alberghiere, Logistics & Industry, Musei e gallerie, Uffici, Esercizi commerciali, Residential & Consumer |
| ETIM Class           | EC000533                                                                                                                        |
| Carico massimo (A)   | 10                                                                                                                              |
| Input                | Microwave, Lux, IR                                                                                                              |
| Input protocol       | Microwave sensor, IR Signal, Lux sensor                                                                                         |
| Protocollo in uscita | Switched                                                                                                                        |
| Numero di canali     | 1                                                                                                                               |
| IP rating            | IP40                                                                                                                            |
| Product EAN number   | 5410288415482                                                                                                                   |

## TABELLA DATI

### Dati generali

|                                  |                                                                                                                                 |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Nome prodotto                    | Ceiling mounted MW detector 10m range. Lux level sensing & time delay function (Z1)                                             |
| Configurato senza PC             | Yes                                                                                                                             |
| Tecnologia                       | Controls                                                                                                                        |
| Montaggio                        | Ceiling recessed mounting                                                                                                       |
| Environment                      | Interior                                                                                                                        |
| General application              | Istruzione, Strutture alberghiere, Logistics & Industry, Musei e gallerie, Uffici, Esercizi commerciali, Residential & Consumer |
| Operating temperature range (°C) | -10°C...+50°C                                                                                                                   |
| ETIM Class                       | EC000533                                                                                                                        |

### Dati elettrici

|                      |                                         |
|----------------------|-----------------------------------------|
| Carico massimo (A)   | 10                                      |
| Input                | Microwave, Lux, IR                      |
| Input protocol       | Microwave sensor, IR Signal, Lux sensor |
| Protocollo in uscita | Switched                                |

## Microwave detectors - Ceiling-mounted and tilt adjustable

*Ceiling mounted MW detector 10m range. Lux level sensing & time delay function (Z1)*

0041548

|                        |          |
|------------------------|----------|
| Numero di canali       | 1        |
| Tensione di rete (V)   | 220-240V |
| Frequenza di rete (HZ) | 50       |

### Dati dimensionali

|                                      |       |
|--------------------------------------|-------|
| IP rating                            | IP40  |
| Lunghezza nominale del prodotto (mm) | 45    |
| Larghezza nominale prodotto (mm)     | 86    |
| Nominal Product Height (mm)          | 86    |
| Peso (Kg)                            | 0.113 |
| Recessed Depth (mm)                  | 23    |

### Dati di imballo

|                                      |                |
|--------------------------------------|----------------|
| Tipologia imballo singolo            | Carton         |
| Product EAN number                   | 5410288415482  |
| Lunghezza imballo singolo (mm)       | 9.0            |
| Larghezza imballo singolo (cm)       | 5.0            |
| Packaging single depth (cm)          | 9.0            |
| DUN14 (outer)                        | 15410288415489 |
| Quantità per imballo esterno         | 100            |
| Packaging outer length / height (cm) | 52.0           |
| Packaging outer width (cm)           | 37.0           |
| Packaging outer depth (cm)           | 37.0           |

### Dati di sicurezza

|                                       |        |
|---------------------------------------|--------|
| Temperatura ottimale di utilizzo (°C) | -10-50 |
|---------------------------------------|--------|

## DISEGNI TECNICI

