

Microwave detectors - Wall-mounted

Wall mounted MW detector 30m range - lux sensing & time delay (Z2) IP66
0041565

Image not found.

Caratteristiche prodotto

- Wall mounted microwave presence detector. 30m detection range. Low number of detectors needed to cover a large area. Lux-level sensing. Adjustable time delay. Self contained unit. No external control making installation quicker. Multiples can be wired in parallel for L-shaped corridors. Programmable using programming handset. IP66 for moisture sensitive areas. Region 2 configuration = Rest of Europe excluding UK, France, Portugal, Germany, Switzerland, Austria, Slovakia, Ireland.

PANORAMICA DEL PRODOTTO

Nome prodotto	Wall mounted MW detector 30m range - lux sensing & time delay (Z2) IP66
Tecnologia	Controls
Montaggio	Wall surface mounted
Environment	Interior/Exterior
General application	Istruzione, Strutture alberghiere, Logistics & Industry, Musei e gallerie, Uffici, Esercizi commerciali, Residential & Consumer
ETIM Class	EC000533
Carico massimo (A)	10
Input	Microwave, Lux, IR
Input protocol	Microwave sensor, IR Signal, Lux sensor
Protocollo in uscita	Switched
Numero di canali	1
IP rating	IP66
Product EAN number	5410288415659

TABELLA DATI

Dati generali

Nome prodotto	Wall mounted MW detector 30m range - lux sensing & time delay (Z2) IP66
Configurato senza PC	Yes
Tecnologia	Controls
Montaggio	Wall surface mounted
Environment	Interior/Exterior
General application	Istruzione, Strutture alberghiere, Logistics & Industry, Musei e gallerie, Uffici, Esercizi commerciali, Residential & Consumer
Operating temperature range (°C)	-10°C...+50°C
ETIM Class	EC000533

Dati elettrici

Carico massimo (A)	10
Input	Microwave, Lux, IR
Input protocol	Microwave sensor, IR Signal, Lux sensor
Protocollo in uscita	Switched
Numero di canali	1
Tensione di rete (V)	220-240V

Microwave detectors - Wall-mounted

Wall mounted MW detector 30m range - lux sensing & time delay (Z2) IP66
0041565

Frequenza di rete (HZ)	50
------------------------	----

Dati dimensionali

IP rating	IP66
Lunghezza nominale del prodotto (mm)	63
Larghezza nominale prodotto (mm)	110
Nominal Product Height (mm)	110
Peso (Kg)	0.11

Dati di imballo

Tipologia imballo singolo	Carton
Product EAN number	5410288415659
Lunghezza imballo singolo (mm)	9.0
Larghezza imballo singolo (cm)	5.0
Packaging single depth (cm)	9.0
Quantità per imballo esterno	100
Packaging outer length / height (cm)	52.0
Packaging outer width (cm)	37.0
Packaging outer depth (cm)	37.0

Dati di sicurezza

Temperatura ottimale di utilizzo (°C)	-10-50
---------------------------------------	--------

DISEGNI TECNICI