

Microwave detectors - Ceiling-mounted and tilt adjustable

Ceiling mounted MW detector 10m range. Lux level sensing & time delay function (Z1) IP66

0041566

Image not found.

Caratteristiche prodotto

- Ceiling mounted microwave presence detector. 10m detection range. Lux-level sensing. Dual sensitivity configurable ON and OFF motion sensitivity. Self contained unit. No external control boxes saves time on installation. Made from robust materials. Programmable using programming handsets. IP66 for moisture sensitive areas. Region 2 configuration = Rest of Europe excluding UK, France, Portugal, Germany, Switzerland, Austria, Slovakia, Ireland.

PANORAMICA DEL PRODOTTO

Nome prodotto	Ceiling mounted MW detector 10m range. Lux level sensing & time delay function (Z1) IP66
Tecnologia	Controls
Montaggio	Ceiling recessed mounting
Environment	Interior/Exterior
General application	Istruzione, Strutture alberghiere, Logistics & Industry, Musei e gallerie, Uffici, Esercizi commerciali, Residential & Consumer
ETIM Class	EC000533
Carico massimo (A)	10
Input	Microwave, Lux, IR
Input protocol	Microwave sensor, IR Signal, Lux sensor
Protocollo in uscita	Switched
Numero di canali	1
IP rating	IP66
Product EAN number	5410288415666

TABELLA DATI

Dati generali

Nome prodotto	Ceiling mounted MW detector 10m range. Lux level sensing & time delay function (Z1) IP66
Configurato senza PC	Yes
Tecnologia	Controls
Montaggio	Ceiling recessed mounting
Environment	Interior/Exterior
General application	Istruzione, Strutture alberghiere, Logistics & Industry, Musei e gallerie, Uffici, Esercizi commerciali, Residential & Consumer
Operating temperature range (°C)	-10°C...+50°C
ETIM Class	EC000533

Dati elettrici

Carico massimo (A)	10
Input	Microwave, Lux, IR
Input protocol	Microwave sensor, IR Signal, Lux sensor
Protocollo in uscita	Switched
Numero di canali	1
Tensione di rete (V)	220-240V

Microwave detectors - Ceiling-mounted and tilt adjustable

*Ceiling mounted MW detector 10m range. Lux level sensing & time delay function
(Z1) IP66*

0041566

Frequenza di rete (HZ)	50
------------------------	----

Dati dimensionali

IP rating	IP66
Lunghezza nominale del prodotto (mm)	63
Larghezza nominale prodotto (mm)	110
Nominal Product Height (mm)	110
Peso (Kg)	0.113

Dati di imballo

Tipologia imballo singolo	Carton
Product EAN number	5410288415666
Lunghezza imballo singolo (mm)	9.0
Larghezza imballo singolo (cm)	5.0
Packaging single depth (cm)	9.0
Quantità per imballo esterno	100
Packaging outer length / height (cm)	52.0
Packaging outer width (cm)	37.0
Packaging outer depth (cm)	37.0

Dati di sicurezza

Temperatura ottimale di utilizzo (°C)	-10-50
---------------------------------------	--------

DISEGNI TECNICI