

SylSafe Bay  
SylSafe Bay RT C EMC NM MS  
0041743



Caratteristiche prodotto

- SylSafe Bay RT C EMC NM MS is a dust and waterproof surface mounted emergency luminaire for industrial applications. Escape route optics for standard mounting heights <4m. Non-maintained version for central battery systems. 200lm, 3W, IK03, IP65. Power Factor 0.44. Class II electrical construction.



PANORAMICA DEL PRODOTTO

|                                 |                                                                                                         |
|---------------------------------|---------------------------------------------------------------------------------------------------------|
| Nome prodotto                   | SylSafe Bay RT C EMC NM MS                                                                              |
| Tecnologia                      | LED                                                                                                     |
| Type                            | LED                                                                                                     |
| Montaggio                       | Ceiling surface mounting                                                                                |
| General application             | Uffici, Strutture alberghiere, Esercizi commerciali, Musei e gallerie, Istruzione, Logistics & Industry |
| ETIM Class                      | EC001957                                                                                                |
| Garanzia                        | 5 years                                                                                                 |
| Fixture luminous flux (lm)      | 200                                                                                                     |
| Luminaire efficacy (lm/W)       | 67                                                                                                      |
| Temperatura di colore (K)       | 5700                                                                                                    |
| CRI (Ra)                        | 75                                                                                                      |
| Gruppo di rischio fotobiologico | RG1                                                                                                     |
| Luminous flux (emergency) (lm)  | 200                                                                                                     |
| Lampada inclusa                 | INTEGRATED LED                                                                                          |
| Electrical protection           | Classe II                                                                                               |
| Colore corpo lampada            | Bianco                                                                                                  |
| IP rating                       | IP65                                                                                                    |
| IK rating                       | IK03                                                                                                    |
| Product EAN number              | 5410288417431                                                                                           |

TABELLA DATI

|                            |                                                                                                         |
|----------------------------|---------------------------------------------------------------------------------------------------------|
| Dati generali              |                                                                                                         |
| Nome prodotto              | SylSafe Bay RT C EMC NM MS                                                                              |
| Tecnologia                 | LED                                                                                                     |
| Type                       | LED                                                                                                     |
| Montaggio                  | Ceiling surface mounting                                                                                |
| General application        | Uffici, Strutture alberghiere, Esercizi commerciali, Musei e gallerie, Istruzione, Logistics & Industry |
| ETIM Class                 | EC001957                                                                                                |
| Garanzia                   | 5 years                                                                                                 |
| Dati ottici                |                                                                                                         |
| Fixture luminous flux (lm) | 200                                                                                                     |

## SylSafe Bay

SylSafe Bay RT C EMC NM MS

0041743

|                                 |      |
|---------------------------------|------|
| Luminaire efficacy (lm/W)       | 67   |
| Temperatura di colore (K)       | 5700 |
| CRI (Ra)                        | 75   |
| Gruppo di rischio fotobiologico | RG1  |
| Luminous flux (emergency) (lm)  | 200  |
| Emergency duration (h)          | 3    |

### Dati elettrici

|                        |                |
|------------------------|----------------|
| Lampada inclusa        | INTEGRATED LED |
| Tensione di rete (V)   | 230-240V       |
| Lamp power factor      | 0.44           |
| Electrical protection  | Classe II      |
| Control gear required  | Sì             |
| Drive current (mA)     | 46             |
| Nominal Frequency (Hz) | 50/60Hz        |

### Dati dimensionali

|                                      |        |
|--------------------------------------|--------|
| Colore corpo lampada                 | Bianco |
| IP rating                            | IP65   |
| IK rating                            | IK03   |
| Lunghezza nominale del prodotto (mm) | 197    |
| Larghezza nominale prodotto (mm)     | 197    |
| Nominal Product Height (mm)          | 53     |
| Peso (Kg)                            | 0.588  |

### Dati di imballo

|                                      |                |
|--------------------------------------|----------------|
| Tipologia imballo singolo            | Carton         |
| Product EAN number                   | 5410288417431  |
| Lunghezza imballo singolo (mm)       | 23.0           |
| Larghezza imballo singolo (cm)       | 15.0           |
| Packaging single depth (cm)          | 7.0            |
| DUN14 (outer)                        | 05410288417431 |
| Quantità per imballo esterno         | 5              |
| Packaging outer length / height (cm) | 42.2           |
| Packaging outer width (cm)           | 25.2           |
| Packaging outer depth (cm)           | 13.2           |

## FOTOMETRIA

## DISEGNI TECNICI