

SylSafe Twin
SylSafe Twin TS C EM3 NM DA
0041770

Image not found.

Caratteristiche prodotto

- SylSafe Twin TS C EM3 NM DA is a dust and waterproof wall mounted twin LED projector for industrial applications. Two individually adjustable heads each delivering 200Lm. White housing colour. Non-maintained 3hr emergency operation with NiCd rechargeable battery. Recharge period 24 hours. Self testing with DALI monitoring capability. 400Lm, 3.23W, IK03, IP65, Power Factor 0.6. Class I electrical construction.



PANORAMICA DEL PRODOTTO

Nome prodotto	SylSafe Twin TS C EM3 NM DA
Tecnologia	LED
Type	LED
Montaggio	Ceiling surface mounting
General application	Logistics & Industry
ETIM Class	EC001957
Garanzia	5 years
Fixture luminous flux (lm)	400
Luminaire efficacy (lm/W)	124
Temperatura di colore (K)	5700
CRI (Ra)	70
Gruppo di rischio fotobiologico	RG0
Luminous flux (emergency) (lm)	334
Lampada inclusa	INTEGRATED LED
Electrical protection	Classe I
Colore corpo lampada	Bianco
IP rating	IP65
IK rating	IK03
Product EAN number	5410288417707

TABELLA DATI

Dati generali	
Nome prodotto	SylSafe Twin TS C EM3 NM DA
Tecnologia	LED
Type	LED
Montaggio	Ceiling surface mounting
General application	Logistics & Industry
ETIM Class	EC001957
Garanzia	5 years
Dati ottici	
Fixture luminous flux (lm)	400
Luminaire efficacy (lm/W)	124

SylSafe Twin

SylSafe Twin TS C EM3 NM DA

0041770

Temperatura di colore (K)	5700
CRI (Ra)	70
Gruppo di rischio fotobiologico	RG0
Luminous flux (emergency) (lm)	334
Emergency duration (h)	3

Dati elettrici

Lampada inclusa	INTEGRATED LED
Tensione di rete (V)	230-240V
Lamp power factor	0.6
Electrical protection	Classe I
Control gear required	Si
Drive current (mA)	25
Nominal Frequency (Hz)	50/60Hz

Dati dimensionali

Colore corpo lampada	Bianco
IP rating	IP65
IK rating	IK03
Lunghezza nominale del prodotto (mm)	280
Larghezza nominale prodotto (mm)	87
Nominal Product Height (mm)	300
Peso (Kg)	1.7

Dati di imballo

Tipologia imballo singolo	Carton
Product EAN number	5410288417707
Lunghezza imballo singolo (mm)	30.3
Larghezza imballo singolo (cm)	28.2
Packaging single depth (cm)	9.2
DUN14 (inner)	05410288417707
Quantità per imballo esterno	5
Packaging outer length / height (cm)	49.5
Packaging outer width (cm)	30.0
Packaging outer depth (cm)	32.5

FOTOMETRIA

DISEGNI TECNICI