

Emergency KITs

EMERGENCY PACK SELF TEST/DALI MONITORING 50V-200V

0046603



Caratteristiche prodotto

- The emergency kit enables conversion of general lighting for emergency operation. It is used for driving luminaires with forward voltages (Vf) of 50V to 200V, and built-in adaptability that allows for optimum output current based on the forward voltage of the specific light engine for a more precise match to the controlled LED scheme. Features: Suitable for independent mounting, Auto load detecting, Compatible with leading brands of mains drivers, SmartCharge technology for NiMH batteries, Test-switch function, Battery deep-discharge protection, Compatible with NiMH batteries, 3-hour rated emergency duration, Supply current (max) 25mA. Ambient temperature (ta): 0°C to +35°C. Max case temperature (tc) +70°C. Conductor size : 0.2 to 1.5mm². DALI functionality. NiMH battery. Product contains a charging regime that prolongs battery life and reduces parasitic power consumption during the product life cycle. By controlling battery temperature this results in energy saving and reduction in maintenance costs throughout the premises.



PANORAMICA DEL PRODOTTO

Nome prodotto	EMERGENCY PACK SELF TEST/DALI MONITORING 50V-200V
Tecnologia	Accessori
Environment	Interior
General application	Istruzione, Strutture alberghiere, Uffici, Esercizi commerciali
ETIM Class	EC000471
Garanzia	1 year
Product EAN number	5410288466033

TABELLA DATI

Dati generali

Nome prodotto	EMERGENCY PACK SELF TEST/DALI MONITORING 50V-200V
Tecnologia	Accessori
Environment	Interior
General application	Istruzione, Strutture alberghiere, Uffici, Esercizi commerciali
ETIM Class	EC000471
Garanzia	1 year

Dati dimensionali

Peso (Kg)	0.47
-----------	------

Dati di imballo

Tipologia imballo singolo	Carton
Product EAN number	5410288466033
Lunghezza imballo singolo (mm)	28.5
Larghezza imballo singolo (cm)	10.0
Packaging single depth (cm)	4.5
Quantità per imballo interno	1
DUN14 (outer)	05410288466033
Quantità per imballo esterno	25
Packaging outer length / height (cm)	46.0

Emergency KITs

EMERGENCY PACK SELF TEST/DALI MONITORING 50V-200V

0046603

Packaging outer width (cm)	31.0
Packaging outer depth (cm)	30.0

Dati di sicurezza

Utilizzabile solo in applicazioni asciutte	Sì
--	----

FOTOMETRIA

DISEGNI TECNICI

