


PIXO LINE 1500 UGR19 840 NERO

Codice n. 0007826

SYLVANIA


PROTM



Pixo Line is a linear track system, adds flexibility to any space due the variety of product options Offers an easy installation with two separate modules Push-in/push-out mechanism with GR6d-15 connector Compatible with Zhaga Book 14 Aluminium body, plastic end caps,aluminised plastic low glare optics in a single line configuration, light beam angle:70° Textured black finishing colour. Light color temperature: 4000K, neutral white, max. system power: 50W Max. fixture lumen output: 7500lm, efficacy: 150lm/W, Ra80 typical, LED chromacity: 3 step MacAdam ellipse (SDCM3), IR/UV free light source without heat radiation Multipower driver module with 8 power settings meet all installation needs with one single product, selection and setting on driver - between 17W (350mA), 19W (400mA), 24W (500mA), 29W (600mA), 34W (700mA), 38W (800mA), 43W (900mA), 50W (1050mA) Suitable for installation on 3-circuit tracks, please check compatibility list on the instruction sheet. Compatible with OneTrack Electrical protection: Class III. Degree of protection: IP20, suitable for indoor environment only Light modules should be combined with suitable in-track drivers Nominal product dimensions: L.1464mmx37.4mmx37mm

Dati tecnici

Dimensioni (mm)



Fotometrie

0.5	0.64 0.70	E107 E108 E109	32.7° 34.8° 34.8°	8717 288 2427
1.0	1.28 1.39	E107 E108 E109	32.7° 34.8° 34.8°	2179 687 607
1.5	1.90 2.09	E107 E108 E109	32.7° 34.8° 34.8°	969 279 270
2.0	2.57 2.78	E107 E108 E109	32.7° 34.8° 34.8°	545 167 152
2.5	3.21 3.48	E107 E108 E109	32.7° 34.8° 34.8°	368 100 97
3.0	3.85 4.17	E107 E108 E109	32.7° 34.8° 34.8°	242 71 67

Distance [m] Cone diameter [m] Illuminance [lx]

— C2 - C180 (Half beam angle: 65.6°)

— C50 - C270 (Half beam angle: 65.4°)

PIXO LINE 1500 UGR19 840 NERO

Codice n. 0007826

SYLVANIA

Dati dimensionali

Colore del prodotto	Nero
Classificazione IP	IP20
Classificazione IK	IK03
Lunghezza nominale del prodotto (mm)	1464
Larghezza nominale prodotto (mm)	37
Altezza nominale prodotto (mm)	37.4
Peso (Kg)	0.9

Dati di imballo

Codice EAN prodotto	5410288078267
Lunghezza/altezza imballo singolo (cm)	147.0
Larghezza imballo singolo (cm)	4.3
Profondità imballo interno (cm) (singolo)	4.3
DUN14_2	15410288078264
Quantità per imballo esterno	10
Lunghezza/ Altezza imballo esterno (cm)	149.0
Packaging outer width (cm)	24.0
Profondità imballo esterno (cm)	11.0

Dati di sicurezza

Test del filo incandescente (°)	650
Temperatura ottimale di utilizzo (°C)	-20-40