

PIR Detectors - Ceiling-mounted

Compact PIR detector - lux sensing. Time delay - IP55

0041541



Caratteristiche prodotto

- PIR sensor with switching capability. IP55 rated for damp areas. On/off switching via lux sensing. Dual sensitivity. Absence/presence detection. Adjustable time delay (10sec to 99min). Up to 7m detection radius at 2.8m mounting height. Programmable via handset. Mounting accessories available. Can be connected in parallel for larger areas and L-shaped corridors. Up to 10A load.



PANORAMICA DEL PRODOTTO

Nome prodotto	Compact PIR detector - lux sensing. Time delay - IP55
Tecnologia	Controls
Montaggio	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Istruzione, Strutture alberghiere, Logistics & Industry, Musei e gallerie, Uffici, Esercizi commerciali, Residential & Consumer
ETIM Class	EC000533
Carico massimo (A)	10
Input	PIR, IR, Lux
Input protocol	PIR Sensor, IR Signal, Lux sensor
Protocollo in uscita	Switched
Numero di canali	1
IP rating	IP55
Product EAN number	5410288415413

TABELLA DATI

Dati generali

Nome prodotto	Compact PIR detector - lux sensing. Time delay - IP55
Configurato senza PC	Yes
Tecnologia	Controls
Montaggio	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Istruzione, Strutture alberghiere, Logistics & Industry, Musei e gallerie, Uffici, Esercizi commerciali, Residential & Consumer
Operating temperature range (°C)	-10°C...+35°C
ETIM Class	EC000533

Dati elettrici

Carico massimo (A)	10
Input	PIR, IR, Lux
Input protocol	PIR Sensor, IR Signal, Lux sensor
Protocollo in uscita	Switched
Numero di canali	1

PIR Detectors - Ceiling-mounted

Compact PIR detector - lux sensing. Time delay - IP55

0041541

Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240

Dati dimensionali

IP rating	IP55
Lunghezza nominale del prodotto (mm)	76
Larghezza nominale prodotto (mm)	76
Nominal Product Height (mm)	68.5
Cutout Dimensions (W x L in mm or Diameter in mm)	64
Peso (Kg)	0.104
Recessed Depth (mm)	65

Dati di imballo

Tipologia imballo singolo	Carton
Product EAN number	5410288415413
Lunghezza imballo singolo (mm)	9.5
Larghezza imballo singolo (cm)	9.5
Packaging single depth (cm)	7.5
DUN14 (outer)	15410288415410
Quantità per imballo esterno	100
Packaging outer length / height (cm)	47.0
Packaging outer width (cm)	47.0
Packaging outer depth (cm)	52.0

Dati di sicurezza

Temperatura ottimale di utilizzo (°C)	-10-35
---------------------------------------	--------

DISEGNI TECNICI

