

Microwave detectors - Ceiling-mounted and tilt adjustable

Ceiling recessed -mounted microwave detector Direct Dim. DALI / DSI

0041557



Caratteristiche prodotto

- Ceiling recessed microwave presence/absence detector. Up to 16m detection range. Direct dimming using DALI to control up to 20 luminaires. Lux level sensing. Time delay function. Infrared override. Dual sensitivity offering configurable ON and OFF motion sensitivity. Programmable via programming handset. Range of accessories available include backboxes. Lamp burn in function. Scene setting and recall capabilities using user handset. Maintained illuminance capabilities. Two channel flexibility: One dimmed + one switched. IP40



PANORAMICA DEL PRODOTTO

Nome prodotto	Ceiling recessed -mounted microwave detector Direct Dim. DALI / DSI
Tecnologia	Controls
Montaggio	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Istruzione, Strutture alberghiere, Logistics & Industry, Musei e gallerie, Uffici, Esercizi commerciali, Residential & Consumer
ETIM Class	EC000533
Garanzia	3 years
Carico massimo (A)	10
Input	Microwave, Lux, IR
Input protocol	Microwave sensor, IR Signal, Lux sensor
Protocollo in uscita	DALI
Numero di canali	2
IP rating	IP40
Product EAN number	5410288415574

TABELLA DATI

Dati generali

Nome prodotto	Ceiling recessed -mounted microwave detector Direct Dim. DALI / DSI
Configurato senza PC	Yes
Tecnologia	Controls
Montaggio	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Istruzione, Strutture alberghiere, Logistics & Industry, Musei e gallerie, Uffici, Esercizi commerciali, Residential & Consumer
Operating temperature range (°C)	-10°C...+50°C
ETIM Class	EC000533
Garanzia	3 years

Dati elettrici

Carico massimo (A)	10
--------------------	----

Microwave detectors - Ceiling-mounted and tilt adjustable

Ceiling recessed -mounted microwave detector Direct Dim. DALI / DSI

0041557

Input	Microwave, Lux, IR
Input protocol	Microwave sensor, IR Signal, Lux sensor
Protocollo in uscita	DALI
Numero di canali	2
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240

Dati dimensionali

IP rating	IP40
Lunghezza nominale del prodotto (mm)	76
Larghezza nominale prodotto (mm)	76
Nominal Product Height (mm)	73
Peso (Kg)	0.124
Recessed Depth (mm)	65

Dati di imballo

Tipologia imballo singolo	Carton
Product EAN number	5410288415574
Lunghezza imballo singolo (mm)	9.5
Larghezza imballo singolo (cm)	9.5
Packaging single depth (cm)	7.5
Quantità per imballo esterno	100
Packaging outer length / height (cm)	47.0
Packaging outer width (cm)	47.0
Packaging outer depth (cm)	52.0

Dati di sicurezza

Temperatura ottimale di utilizzo (°C)	-10-50
---------------------------------------	--------

DISEGNI TECNICI

