

Microwave detectors - Ceiling-mounted and tilt adjustable
Ceiling mounted Adjustable MW detector - lux sensing & time delay (Z2)
0041579



Caratteristiche prodotto

- Adjustable/tiltable ceiling recessed microwave presence/absence detector. Lux level sensing. Time delay function. Infrared override. Dual sensitivity offers configurable ON and OFF motion sensitivity. Programmable using programming handsets. Wide range of accessories including surface mounting backboxes and wall mounting bracket. Multiples can be wired in parallel for L-shaped corridors. IP40. Region 2 configuration = Rest of Europe excluding UK, France, Portugal, Germany, Switzerland, Austria, Slovakia, Ireland.



PANORAMICA DEL PRODOTTO

Nome prodotto	Ceiling mounted Adjustable MW detector - lux sensing & time delay (Z2)
Tecnologia	Controls
Montaggio	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Istruzione, Strutture alberghiere, Logistics & Industry, Musei e gallerie, Uffici, Esercizi commerciali, Residential & Consumer
ETIM Class	EC000533
Garanzia	3 years
Carico massimo (A)	10
Input	Microwave, Lux, IR
Input protocol	Microwave sensor, IR Signal, Lux sensor
Protocollo in uscita	Switched
Numero di canali	1
IP rating	IP40
Product EAN number	5410288415796

TABELLA DATI

Dati generali	
Nome prodotto	Ceiling mounted Adjustable MW detector - lux sensing & time delay (Z2)
Configurato senza PC	Yes
Tecnologia	Controls
Montaggio	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Istruzione, Strutture alberghiere, Logistics & Industry, Musei e gallerie, Uffici, Esercizi commerciali, Residential & Consumer
Operating temperature range (°C)	-10°C...+50°C
ETIM Class	EC000533
Garanzia	3 years
Dati elettrici	
Carico massimo (A)	10
Input	Microwave, Lux, IR
Input protocol	Microwave sensor, IR Signal, Lux sensor

Microwave detectors - Ceiling-mounted and tilt adjustable

Ceiling mounted Adjustable MW detector - lux sensing & time delay (Z2)

0041579

Protocollo in uscita	Switched
Numero di canali	1
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240

Dati dimensionali

IP rating	IP40
Lunghezza nominale del prodotto (mm)	85
Larghezza nominale prodotto (mm)	85
Nominal Product Height (mm)	92
Cutout Dimensions (W x L in mm or Diameter in mm)	74
Peso (Kg)	0.15
Recessed Depth (mm)	92

Dati di imballo

Tipologia imballo singolo	Carton
Product EAN number	5410288415796
Lunghezza imballo singolo (mm)	10.0
Larghezza imballo singolo (cm)	10.0
Packaging single depth (cm)	10.0
Quantità per imballo esterno	1
Packaging outer length / height (cm)	63.0
Packaging outer width (cm)	47.0
Packaging outer depth (cm)	47.0

Dati di sicurezza

Temperatura ottimale di utilizzo (°C)	-10-50
---------------------------------------	--------

DISEGNI TECNICI

