

Microwave detectors - Ceiling-mounted and tilt adjustable

Ceiling mounted Adjustable MW detector - lux sensing & time delay (Z3) 1-10 DIM

0041584



Caratteristiche prodotto

- Adjustable/tiltable ceiling recessed microwave presence/absence detector. 1-10V Direct dimming for controlling up to 10 luminaires. Lux level sensing. Time delay function. Infrared override. Dual sensitivity offers configurable ON and OFF motion sensitivity. Programmable using programming handsets. Wide range of accessories including surface mounting backboxes and wall mounting bracket. Maintained illuminance capabilities. Scene setting and recall using user handset. Lamp burn in feature. IP40. Region 3 configuration = France, Portugal, Switzerland.



PANORAMICA DEL PRODOTTO

Nome prodotto	Ceiling mounted Adjustable MW detector - lux sensing & time delay (Z3) 1-10 DIM
Tecnologia	Controls
Montaggio	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Istruzione, Strutture alberghiere, Logistics & Industry, Musei e gallerie, Uffici, Esercizi commerciali, Residential & Consumer
ETIM Class	EC000533
Garanzia	3 years
Carico massimo (A)	10
Input	Microwave, Lux, IR
Input protocol	Microwave sensor, IR Signal, Lux sensor
Protocollo in uscita	1-10V
Numero di canali	2
IP rating	IP40
Product EAN number	5410288415840

TABELLA DATI

Dati generali

Nome prodotto	Ceiling mounted Adjustable MW detector - lux sensing & time delay (Z3) 1-10 DIM
Configurato senza PC	Yes
Tecnologia	Controls
Montaggio	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Istruzione, Strutture alberghiere, Logistics & Industry, Musei e gallerie, Uffici, Esercizi commerciali, Residential & Consumer
Operating temperature range (°C)	-10°C...+50°C
ETIM Class	EC000533
Garanzia	3 years

Dati elettrici

Carico massimo (A)	10
Input	Microwave, Lux, IR
Input protocol	Microwave sensor, IR Signal, Lux sensor

Microwave detectors - Ceiling-mounted and tilt adjustable

Ceiling mounted Adjustable MW detector - lux sensing & time delay (Z3) 1-10 DIM
0041584

Protocollo in uscita	1-10V
Numero di canali	2
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240

Dati dimensionali

IP rating	IP40
Lunghezza nominale del prodotto (mm)	85
Larghezza nominale prodotto (mm)	85
Nominal Product Height (mm)	92
Cutout Dimensions (W x L in mm or Diameter in mm)	74
Peso (Kg)	0.155
Recessed Depth (mm)	92

Dati di imballo

Tipologia imballo singolo	Carton
Product EAN number	5410288415840
Lunghezza imballo singolo (mm)	10.0
Larghezza imballo singolo (cm)	10.0
Packaging single depth (cm)	10.0
Quantità per imballo esterno	96
Packaging outer length / height (cm)	63.0
Packaging outer width (cm)	47.0
Packaging outer depth (cm)	47.0

Dati di sicurezza

Temperatura ottimale di utilizzo (°C)	-10-50
---------------------------------------	--------

DISEGNI TECNICI

