

Dati tecnici

TL71 Set di puntali



Caratteristiche principali

- Due puntali al silicone (rosso e nero) con connettori ad angolo retto
- Consigliati per le misure in μV
- CAT II, 1000 V, 10 A
- CAT III 1000 V, CAT IV 600V solo con coperchio protettivo
- 1 anno di garanzia

Descrizione generale del prodotto: TL71 Set di puntali

The Fluke TL71 Premium Multimeter Test Lead Set is a pair of comfort grip probes (red and black) with flexible silicone-insulated, right-angle test leads. These distinctive comfort grip probes are heat and cold resistant.

As with all Fluke products, these test leads undergo a battery of safety tests to be rated at:

CAT II 1000 V, 10 A rating

CAT III 1000 V, CAT IV 600V with protective cap

The WearGuard™ test lead indicator shows wear and tear easier. It exposes a contrasting color when the leads are damaged and need to be replaced. Silicone-insulated leads have superior flexibility in cold temperatures and resistance to high temperatures.

The Fluke TL71 Premium Test Leads are compatible with all instruments that accept standard 4 mm (0.16 in) shrouded

banana connectors. Some of the compatible tools include:

Fluke 902 FC True-RMS HVAC Clamp Meter

Fluke 87V Industrial Multimeter

Fluke 115 Field Technicians Digital Multimeter

Fluke 787B ProcessMeter™

These test leads come with a one-year warranty.

Dati tecnici: TL71 Set di puntali

Lead Length	1.2 (4 ft), 2mm diameter probe tip
Category Rating	CAT II 1000 V, CAT III 1000 V, CAT IV 600 V, 10 A max
Operating temperature	-20°C to 55°C (-4°F to 131°F), 90 % RH altitude: 2000 m (6,562 ft)

Modelli



Fluke TL71

Test Lead Set

- One pair (red, black) comfort grip probes with silicone insulated, right-angle test leads
- Recommended for μV measurements
- CAT II 1000 V, 10 A rating
- CAT III 1000 V, CAT IV 600V only with protective cap
- One year warranty

Fluke. *Keeping your world up and running.®*

Fluke Italia S.r.l.
Viale Lombardia 218
20861 Brugherio (MB)
Tel: +39 02 3600 2000
E-mail: cs.it@fluke.com
www.fluke.it

©2026 Fluke Corporation. Tutti i diritti riservati.
Dati passibili di modifiche senza preavviso.
05/2026

**Non sono ammesse modifiche al presente
documento senza autorizzazione scritta da parte
di Fluke Corporation.**