

Dati tecnici

Fluke AC175 Alligator Clip Set



Caratteristiche principali

- Insulated alligator clips with flexible boots, threaded shaft for secure probe attachment, 7mm jaw opening, and nickel-plated steel contacts
- Provides reliable and secure connections for precise electrical measurements
- Rated CAT II 1000 V, CAT III 1000 V, CAT IV 600 V, 10 A
- see compatible products below

Descrizione generale del prodotto: Fluke AC175 Alligator Clip Set

Modular clips are used with modular test leads to offer additional flexibility to configure your leads to your individual needs. The insulated alligator clip jaws provide a 7 mm opening with flexible boots.

The Fluke AC175 Threaded Alligator Clip Set comes with a one-year warranty and a cat rating of CAT III 1000 V, CAT IV 600 V, 10 A.

This alligator clip set has slide-on alligator clips (red, black) compatible with multiple Fluke test probes:

Fluke TL71 Premium Test Lead Set

Fluke TL75 Hard Point™ Test Lead Set

Fluke TL175 TwistGuard™ Test Leads

Dati tecnici: Fluke AC175 Alligator Clip Set

Jaw opening	7 mm (0.275 in), jaw contact material: nickel-plated steel
Category Rating	CAT III 1000 V, CAT IV 600 V, 10 A
Operating temperature	-20°C to 55°C (-4°F to 131°F)
Environmental Information	Pollution Degree 2, 2000 m altitude

Modelli



Fluke AC175

AC175 Alligator Clip Set

Optional accessories

TL71 Set di puntali

Puntali TL175 TwistGuard™

Fluke TP175 TwistGuard™ Test Probes

TL75 Set di puntali Hard Point

Description

Due puntali al silicone (rosso e nero) con connettori ad angolo retto

La guaina della punta estendibile brevettata è conforme ai nuovi requisiti di sicurezza elettrica per la riduzione dell'esposizione della punta garantendo, al contempo, la flessibilità necessaria per la maggior parte delle misure

The Fluke TP175 TwistGuard® Test Probes have adjustable tip lengths that allow you to work safely in different settings.

Due puntali in PVC (rosso e nero) con connettori a banana ad angolo retto

Fluke. *Keeping your world up and running.®*

Fluke Italia S.r.l.
Viale Lombardia 218
20861 Brugherio (MB)
Tel: +39 02 3600 2000
E-mail: cs.it@fluke.com
www.fluke.it

©2026 Fluke Corporation. Tutti i diritti riservati.
Dati passibili di modifiche senza preavviso.
05/2026

**Non sono ammesse modifiche al presente
documento senza autorizzazione scritta da parte
di Fluke Corporation.**