



N. rif. 671085 | Tipo HTI+254C100

Descrizione: MCB Miniature Circuit Breaker Hti+ C Curve 4 Poles 100A 25kA

EAN 5413656710851

Home > Linea Modulare Plus > Protezione delle linee > Protezione delle linee

Description:

The Hti+ range offers the right High Performance MCB with high-rated breaking capacities and various tripping characteristics. The Hti+ 36 is the ideal solution for applications of up to 36kA of course, also for current ratings of between 80 and 125A. The high-rated breaking capacities of Hti+50 up to 50kA allow electrical distribution systems to be configured and operated safely in an uncomplicated manner. Compact dimensions ensure that energy distribution systems can be set up in a space-saving way.

* Features: - Space saving. Reduce the side of the distribution board to the minimum.- More power. The highest breaking capacity in modular MCB format: 50kA.- High nominal current range of up to 125A.- More safety. Convincing selectivity and back-up properties up to 50kA.- More comfort. Compact and modular with plastic tongue in IP20 terminals.- More flexibility. Thanks to the large product portfolio for a multitude of applications.- More accessories. Add on RCDs, RCBOs, Auxiliaries, Shunt trip, under voltage and rotary handle.

Immagine illustrativa

Descrittori

Category	Protezione delle linee
----------	------------------------

Specifiche

Serie	Protezione delle linee
In (A)	100
Numero di poli	4
Numero di moduli	6
Curva di limitazione	C
Gruppo	Hti+
Gamma	Terziario - Industriale
Attacchi parte superiore	Morsetto con vite
Attacchi parte inferiore	Vite
AC/CC	AC
Omologazioni	CE
Logo	GE
Tensione nominale (2)	240/415
Potere d'interruzione (kA)	25
Capacità terminale: max (mm ²)	70
Durata elettrica	6000
Minima tensione d'impiego Ubmin (V)	12
Capacità terminale: min (mm ²)	50

Classificazione

ETIM 6.0	EC000042
----------	----------