



Connector clips for oval holes

with fir tree

The connector clips used here have been designed for electronic cables and cable sets used in the automotive industry. These parts are related to a connector and then secured to a surface depending on the requirement.

Features and benefits

- Connector easily installed by simply pushing into place
- Connection can be released non-destructive
- Easy assembly, just shuffle manually
- Oval connectors offer twist protection
- Available for a wide variety of panel thicknesses



For a secure fixation simply push the connector by hand on our Connector Clip YCCFT62x122.

Material information on page 22.

TYPE	Drawing	Hole Ø (FH)	Panel Thickness	Width (W)	Length (L)	Height (H)	Material	Colour	EWCAP standard	Article-No.
YCCFT62x122		6.2 x 12.2	0.6 - 6.0	16.0	21.1	18.0	PA66HIRHS	Black (BK)	-	151-00180
YCCFT82x185		8.2 x 18.5	1.5 - 4.5	17.4	28.4	16.0	PA66HIRHS	Black (BK)	EWCAP-005-11	151-01842
CC11		9.0 x 16.0 9.0 x 17.0	0.6 - 6.5	18.2	30.0	20.6	PA66HIRHSUV	Black (BK)	EWCAP-005-11	151-01144
CC12		8.0 x 15.0	0.6 - 6.5	18.3	25.5	22.2	PA66HIRHSUV	Black (BK)	-	151-01136
CC15		12.0 x 17.0	0.6 - 9.0	20.3	30.3	23.6	PA66HIRHSUV	Black (BK)	EWCAP-005-11	151-01199
CC16		8.0 x 14.0 8.0 x 15.0	0.6 - 7.75	18.2	30.0	23.4	PA66HIRHSUV	Black (BK)	EWCAP-005-11	151-01297
CC17		12.0 x 17.0	0.6 - 9.0	20.3	29.9	26.2	PA66HIRHSUV	Black (BK)	EWCAP-005-7	151-01295
CC20		9.0 x 17.0	0.6 - 9.5	20.3	25.5	26.1	PA66HIRHSUV	Black (BK)	EWCAP-005-7	151-01397

All dimensions in mm. Subject to technical changes.



Connector clips for oval holes

with fir tree

TYPE	Drawing	Hole Ø (FH)	Panel Thickness	Width (W)	Length (L)	Height (H)	Material	Colour	EWCAP standard	Article-No.
CCDOP62x122		6.2 x 12.2	0.7 - 5	10.3	20.5	17.7	PA66HIRHS	Black (BK)	-	151-02431
CCLOP62X122		6.2 x 12.2	15.0	19.7	31.2	28.4	PA66HIRHS	Black (BK)	EWCAP-005-23	151-00855
CCOVAL2		6.2 x 12.2 6.5 x 12.5 6.5 x 13.0 7.0 x 12.0	0.6 - 6.0	17.6	29.0	22.4	PA66HIRHSUV	Black (BK)	EWCAP-005-7	151-01108
CCOVAL3		6.2 x 12.2 6.5 x 12.5 6.5 x 13.0 7.0 x 12.0	0.6 - 6.75	19.5	25.2	25.5	PA66HIRHSUV	Black (BK)	EWCAP-005-23	151-01244
CCOVAL4		6.2 x 12.2 6.5 x 12.5 6.5 x 13.0 7.0 x 12.0	0.6 - 6.75	17.6	23.6	21.6	PA66HIRHSUV	Black (BK)	-	151-01246
CCOVAL6		6.2 x 12.2 6.5 x 12.5 6.5 x 13.0 7.0 x 12.0	0.6 - 3.0	17.6	29.3	15.2	PA66HIRHSUV	Black (BK)	EWCAP-005-11	151-01033
CCOVAL		6.2 x 12.2 6.5 x 12.5 6.5 x 13.0 7.0 x 12.0	0.6 - 6.0	17.6	29.3	20.0	PA66HIRHSUV	Black (BK)	EWCAP-005-11	151-00925
CP31DOP		6.2 x 12.2	0.6 - 5.0	-	-	26.1	PA66HIRHS	Black (BK)	-	151-00214
CP21DOP		6.2 x 12.2	0.6 - 5.0	-	-	26.1	PA66HIRHS	Black (BK)	-	151-00465
CP61DOP		6.2 x 12.2	0.6 - 5.0	-	-	26.8	PA66HIRHS	Black (BK)	-	151-00918
3FAKRACCBOX9X17OFT		9.0 x 17.0	0.6 - 2.25	18.2	26.6	28.6	PA66HIRHS	Black (BK)	EWCAP-005-11	133-04068
CC16R		8.0 x 14.0 8.0 x 15.0	0.6 - 3.0	18.2	30.0	23.4	PA66HIRHSUV	Black (BK)	EWCAP-005-11	151-02206
CCPAEDOP6.0x12.0		6.2 x 12.2	0.6 - 6.0	22.5	20.0	17.5	PA66HIRHS	Black (BK)	-	133-01073

All dimensions in mm. Subject to technical changes.



Material Specification Overview

MATERIAL	Material Shortcut	Operating Temperature	Colour**	Flammability	Material Properties*	Material Specifications
Aluminium alloy	AL	-40 °C to +180 °C	Natural (NA)		• Corrosion resistant • Antimagnetic	RoHS
Chloroprene Rubber	CR	-20 °C to +80 °C	Black (BK)		• Weather resistant • High yield strength	RoHS
Ethylene Tetrafluoroethylene (Tefzel®)	E/TFE	-80 °C to +170 °C	Blue (BU)	UL 94 V0	• Resistance to radioactivity • UV resistant, not moisture sensitive • Good chemical resistance to acids, bases, oxidizing agents	RoHS
Polyacetal	POM	-40 °C to +90 °C, (+110 °C, 500 h)	Natural (NA)	UL 94 HB	• Limited brittleness sensitivity • Flexible at low temperature • Not moisture sensitive • Robust on impact	RoHS
Polyamide 11	PA11	-40 °C to +85 °C, (+105 °C, 500 h)	Black (BK)	UL 94 HB	• Bio-plastic, derived from vegetable oil • Strong impact resistance at low temperature • Very low moisture absorption • Weather resistant • Good chemical resistance	HF RoHS
Polyamide 12	PA12	-40 °C to +85 °C, (+105 °C, 500 h)	Black (BK)	UL 94 HB	• Good chemical resistance to acids, bases, oxidizing agents • UV resistant	HF RoHS
Polyamide 4.6	PA46	-40 °C to +130 °C, (+150 °C, 5000 h; +195 °C, 500 h)	Natural (NA), Grey (GY)	UL 94 V2	• Resistance to high temperatures • Very moisture sensitive • Low smoke sensitivity	HF LFH RoHS
Polyamide 6	PA6	-40 °C to +80 °C	Black (BK)	UL 94 V2	• High yield strength	RoHS
Polyamide 6, high impact modified	PA6HIR	-40 °C to +80 °C	Black (BK)	UL 94 HB	• Limited brittleness sensitivity • Higher flexibility at low temperature	RoHS
Polyamide 6.6	PA66	-40 °C to +85 °C, (+105 °C, 500 h)	Black (BK), Natural (NA)	UL 94 V2	• High yield strength	HF RoHS
Polyamide 6.6, glass-fibre reinforced	PA66GF13	-40 °C to +105 °C	Black (BK)	UL 94 HB	• Good resistance to lubricants, fuels, salt water and solvents	HF RoHS
Polyamide 6.6, heat and UV-stabilised	PA66HSUV	-40 °C to +105 °C	Black (BK)	UL 94 V2	• High yield strength • Modified elevated maximum temperature • UV resistant	HF RoHS
Polyamide 6.6, heat stabilised	PA66HS	-40 °C to +105 °C	Black (BK), Natural (NA)	UL 94 V2	• High yield strength • Modified elevated maximum temperature	HF RoHS
Polyamide 6.6, high impact modified	PA66HIR	-40 °C to +80 °C, (+105 °C, 500 h)	Black (BK)	UL 94 HB	• Limited brittleness sensitivity • Higher flexibility at low temperature	RoHS
Polyamide 6.6, high impact modified, heat and UV-stabilised	PA66HIRHSUV	-40 °C to +110 °C	Black (BK)	UL 94 HB	• Limited brittleness sensitivity • Higher flexibility at low temperature • Modified elevated maximum temperature • High yield strength, UV resistant	RoHS
Polyamide 6.6, high impact modified, heat stabilised	PA66HIRHS	-40 °C to +105 °C	Black (BK)	UL 94 HB	• Limited brittleness sensitivity • Higher flexibility at low temperature • Modified elevated maximum temperature	RoHS
Polyamide 6.6, high impact modified, scan black)	PA66HIR(S)	-40 °C to +80 °C, (+105 °C, 500 h)	Black (BK)	UL 94 HB	• Limited brittleness sensitivity • Higher flexibility at low temperature	HF RoHS
Polyamide 6.6, UV-resistant	PA66W	-40 °C to +85 °C, (+105 °C, 500 h)	Black (BK)	UL 94 V2	• High yield strength • UV resistant	HF RoHS

MATERIAL	Material Shortcut	Operating Temperature	Colour**	Flammability	Material Properties*	Material Specifications
Polyamide 6.6, with metal particles	PA66MP	-40 °C to +85 °C, (+105 °C, 500 h)	Blue (BU)	UL 94 HB	• High yield strength • Metal and X-Ray detectable	HF RoHS
Polyamide 6.6, with metal particles	PA66MP+	-40 °C to +85 °C	Blue (BU)	not flame-retardant	• High yield strength • Metal and X-Ray detectable	HF RoHS
Polyamide 6.6 V0	PA66V0	-40 °C to +85 °C	White (WH)	UL 94 V0	• High yield strength • Low smoke emission	HF LFH RoHS
Polyester	SP	-50 °C to +150 °C	Black (BK)		• UV resistant • Good chemical resistance to most acids, bases and oils	HF LFH RoHS
Polyetheretherketone	PEEK	-55 °C to +240 °C	Beige (BGE)	UL 94 V2	• Resistance to radioactivity • Not moisture sensitive • Good chemical resistance to acids, bases, oxidising agents	HF LFH RoHS
Polyethylene	PE	-40 °C to +50 °C	Black (BK), Grey (GY)	UL 94 HB	• Low moisture absorption • Good chemical resistance to most acids, bases, alcohol, oils	HF RoHS
Polyolefin	PO	-40 °C to +90 °C	Black (BK)	UL 94 V0	• Low smoke emissions	HF LFH RoHS
Polypropylene	PP	-40 °C to +115 °C	Black (BK), Natural (NA)	UL 94 HB	• Floats in water • Moderate yield strength • Good chemical resistance to acids, bases and solvents	HF RoHS
Polypropylene, Ethylene Propylene Diene Terpolymer rubber free of Nitrosamine	PP, EPDM	-20 °C to +95 °C	Black (BK)	UL 94 HB	• Good resistance to high temperature • Good chemical and abrasion resistance	HF RoHS
Polypropylene with metal particles	PPMP	-40 °C to +115 °C	Blue (BU)	UL 94 HB	• Metal and X-Ray detectable • Heat resistant • Moderate yield strength • Good chemical resistance	RoHS
Polypropylene with metal particles	PPMP+	-40 °C to +85 °C	Blue (BU)	not flame-retardant	• High yield strength • Metal and X-Ray detectable	HF RoHS
Polyvinylchloride	PVC	-10 °C to +70 °C	Black (BK), Natural (NA)	UL 94 V0	• Low moisture absorption • Good chemical resistance to acids, bases, salts, alcohol, oils	RoHS
Stainless Steel, Stainless Steel	SS304, SS316	-80 °C to +538 °C	Natural (NA)	non-burning	• Corrosion resistant • Antimagnetic • Weather resistant • Chemical resistance • SS316 also resistant against seawater, salt spray and anorganic acids	HF LFH RoHS
Thermoplastic Polyurethane	TPU	-40 °C to +85 °C	Black (BK)	UL 94 HB	• High elasticity • Good chemical resistance to acids, bases and oxidising agents	HF RoHS

Tefzel® is a registered trademark of DuPont. General linguistic usage for cable ties made from raw material E/TFE is Tefzel®-Tie. In addition to Tefzel® from DuPont HellermannTyton also uses equivalent E/TFE raw material from other suppliers.

*These details are only guide values. They should not be regarded as an exhaustive material specification and are no substitute for suitability tests. Please see our datasheets for further details.

HF = Halogen Free

LFH = Limited Fire Hazard

RoHS = Restriction of Hazardous Substances

**Further colours available on request.



= Minimum Loop Tensile Strength
for Cable Ties (newton)

For more material information
please visit our website.