



2-piece fixing ties with pipe clip

twistable 360°

These fixing ties provide the opportunity to attach a wire or hose to an existing harness. Offering a full 360 degrees rotation, the wire/hose can be oriented in any direction in relation to the main harness.


Features and benefits

- Simply clip on a wire or hose
- Fixing clip offers full 360° rotation
- Routed cable can move in any direction in relation to the fixing point



T50SVC5 rotates in any direction.

Material information on page 22.





TYPE	Drawing	Attach to Ø	Width (W)	Length (L)	Bundle Ø max.	N	Material	Colour	Tools	Article-No.
T50SVC5		4.5 - 5.2	4.7	155.0	35.0	222	PA66HS	BK	1-2;4-7;25	155-31202
T50SVC6.5		6.5 - 8.0	4.7	155.0	35.0	222	PA66HS PA66HIRHS	BK	1-2;4-7;25	156-00155
		6.5 - 8.0	4.7	155.0	35.0	222	PA66HS PA66HIRHS	BK	1-2;4-7;25	156-01670
T50SVC3.5		3.45 - 3.55	4.7	155.0	35.0	222	PA66HS PA66HIRHS	BK	1-2;4-7;25	156-00791
T50SVCMOCSM		-	4.7	10.7	5.5	222	PA66HIRHSUV	BK	1-2;4-7;25	156-02239

Recommended Tools: 1=MK10-SB, 2=MK20, 4=MK3PNSP2, 5=EVO7i, 6=MK7P, 7=EVO9i, 25=EVOcut. For more information on toolings please refer to the Application Tooling chapter on page 346.

All dimensions in mm. Subject to technical changes.



twistable 360°

TYPE	Drawing	Attach to Ø	Width (W)	Length (L)	Bundle Ø max.	N	Material	Colour	Tools	Article-No.
T50SVCOC10-14		10.0 - 14.0	4.7	155.0	35.0	222	PA66HS PA66HIRHS	BK	1-2;4-7;25	156-00134
		10.0 - 14.0	4.7	155.0	35.0	222	PA46	GY	1-2;4-7;25	156-01045
T50ROC10-14CBTO-SD-SET		10.0 - 14.0	4.6	202.0	45.0	225	PA66HS PA66HIRHS	BK	1-2;4-6;25	156-02441
T50SMVCOC10-14		10.0 - 14.0	4.7	210.0	50.0	222	PA66HS PA66HIRHS	BK	1-2;4-7;25	156-00128
T50SVCOC15-18		15.0 - 18.0	4.7	155.0	35.0	222	PA66HS PA66HIRHS	BK	1-2;4-7;25	156-00135
T50SMVCOC15-18		15.0 - 18.0	4.7	210.0	50.0	222	PA66HS PA66HIRHS	BK	1-2;4-7;25	156-00129
T50SVCOC19-24.5		19.0 - 24.5	4.7	155.0	35.0	222	PA66HS PA66HIRHS	BK	1-2;4-7;25	156-00136
T50SMVCOC19-24.5		19.0 - 24.5	4.7	210.0	50.0	222	PA46	GY	1-2;4-7;25	156-00577
		19.0 - 24.5	4.7	210.0	50.0	222	PA66HS PA66HIRHS	BK	1-2;4-7;25	156-00130
T50SMVCOC25-31		25.0 - 31.0	4.7	210.0	50.0	222	PA66HS PA66HIRHS	BK	1-2;4-7;25	156-00303
T50SVCOC25-31		25.0 - 31.0	4.7	155.0	35.0	222	PA46 PA66HIRHS	GY, BK	1-2;4-7;25	156-01241
		25.0 - 31.0	4.7	155.0	35.0	222	PA66HS PA66HIRHS	BK	1-2;4-7;25	156-00272
T50SVCOC31-39		31.0 - 39.0	4.7	155.0	35.0	222	PA66HS PA66HIRHS	BK	1-2;4-7;25	156-00273
T50SMVCOC31-39		31.0 - 39.0	4.7	210.0	50.0	222	PA66HS PA66HIRHS	BK	1-2;4-7;25	156-02445
T50SVCOC39-45		39.0 - 45.0	4.7	155.0	35.0	222	PA66HS PA66HIRHS	BK	1-2;4-7;25	156-00137
T50SMVCOC39-45		39.0 - 45.0	4.7	210.0	50.0	222	PA66HS PA66HIRHS	BK	1-2;4-7;25	156-00131
T50SVCOC25.0-31.0ST		25.0 - 31.0	4.7	155.0	35.0	222	PA66HS PA66HIRHS	BK	1-2;4-7;25	156-01074

Recommended Tools: 1=MK10-SB, 2=MK20, 4=MK3PNSP2, 5=EVO7i, 6=MK7P, 7=EVO9i, 25=EVOcut. For more information on toolings please refer to the Application Tooling chapter on page 346.

All dimensions in mm. Subject to technical changes.



Material Specification Overview

MATERIAL	Material Shortcut	Operating Temperature	Colour**	Flammability	Material Properties*	Material Specifications
Aluminium alloy	AL	-40 °C to +180 °C	Natural (NA)		• Corrosion resistant • Antimagnetic	RoHS
Chloroprene Rubber	CR	-20 °C to +80 °C	Black (BK)		• Weather resistant • High yield strength	RoHS
Ethylene Tetrafluoroethylene (Tefzel®)	E/TFE	-80 °C to +170 °C	Blue (BU)	UL 94 V0	• Resistance to radioactivity • UV resistant, not moisture sensitive • Good chemical resistance to acids, bases, oxidizing agents	RoHS
Polyacetal	POM	-40 °C to +90 °C, (+110 °C, 500 h)	Natural (NA)	UL 94 HB	• Limited brittleness sensitivity • Flexible at low temperature • Not moisture sensitive • Robust on impact	RoHS
Polyamide 11	PA11	-40 °C to +85 °C, (+105 °C, 500 h)	Black (BK)	UL 94 HB	• Bio-plastic, derived from vegetable oil • Strong impact resistance at low temperature • Very low moisture absorption • Weather resistant • Good chemical resistance	HF RoHS
Polyamide 12	PA12	-40 °C to +85 °C, (+105 °C, 500 h)	Black (BK)	UL 94 HB	• Good chemical resistance to acids, bases, oxidizing agents • UV resistant	HF RoHS
Polyamide 4.6	PA46	-40 °C to +130 °C, (+150 °C, 5000 h; +195 °C, 500 h)	Natural (NA), Grey (GY)	UL 94 V2	• Resistance to high temperatures • Very moisture sensitive • Low smoke sensitivity	HF LFH RoHS
Polyamide 6	PA6	-40 °C to +80 °C	Black (BK)	UL 94 V2	• High yield strength	RoHS
Polyamide 6, high impact modified	PA6HIR	-40 °C to +80 °C	Black (BK)	UL 94 HB	• Limited brittleness sensitivity • Higher flexibility at low temperature	RoHS
Polyamide 6.6	PA66	-40 °C to +85 °C, (+105 °C, 500 h)	Black (BK), Natural (NA)	UL 94 V2	• High yield strength	HF RoHS
Polyamide 6.6, glass-fibre reinforced	PA66GF13	-40 °C to +105 °C	Black (BK)	UL 94 HB	• Good resistance to lubricants, fuels, salt water and solvents	HF RoHS
Polyamide 6.6, heat and UV-stabilised	PA66HSUV	-40 °C to +105 °C	Black (BK)	UL 94 V2	• High yield strength • Modified elevated maximum temperature • UV resistant	HF RoHS
Polyamide 6.6, heat stabilised	PA66HS	-40 °C to +105 °C	Black (BK), Natural (NA)	UL 94 V2	• High yield strength • Modified elevated maximum temperature	HF RoHS
Polyamide 6.6, high impact modified	PA66HIR	-40 °C to +80 °C, (+105 °C, 500 h)	Black (BK)	UL 94 HB	• Limited brittleness sensitivity • Higher flexibility at low temperature	RoHS
Polyamide 6.6, high impact modified, heat and UV-stabilised	PA66HIRHSUV	-40 °C to +110 °C	Black (BK)	UL 94 HB	• Limited brittleness sensitivity • Higher flexibility at low temperature • Modified elevated maximum temperature • High yield strength, UV resistant	RoHS
Polyamide 6.6, high impact modified, heat stabilised	PA66HIRHS	-40 °C to +105 °C	Black (BK)	UL 94 HB	• Limited brittleness sensitivity • Higher flexibility at low temperature • Modified elevated maximum temperature	RoHS
Polyamide 6.6, high impact modified, scan black)	PA66HIR(S)	-40 °C to +80 °C, (+105 °C, 500 h)	Black (BK)	UL 94 HB	• Limited brittleness sensitivity • Higher flexibility at low temperature	HF RoHS
Polyamide 6.6, UV-resistant	PA66W	-40 °C to +85 °C, (+105 °C, 500 h)	Black (BK)	UL 94 V2	• High yield strength • UV resistant	HF RoHS

MATERIAL	Material Shortcut	Operating Temperature	Colour**	Flammability	Material Properties*	Material Specifications
Polyamide 6.6, with metal particles	PA66MP	-40 °C to +85 °C, (+105 °C, 500 h)	Blue (BU)	UL 94 HB	• High yield strength • Metal and X-Ray detectable	HF RoHS
Polyamide 6.6, with metal particles	PA66MP+	-40 °C to +85 °C	Blue (BU)	not flame-retardant	• High yield strength • Metal and X-Ray detectable	HF RoHS
Polyamide 6.6 V0	PA66V0	-40 °C to +85 °C	White (WH)	UL 94 V0	• High yield strength • Low smoke emission	HF LFH RoHS
Polyester	SP	-50 °C to +150 °C	Black (BK)		• UV resistant • Good chemical resistance to most acids, bases and oils	HF LFH RoHS
Polyetheretherketone	PEEK	-55 °C to +240 °C	Beige (BGE)	UL 94 V2	• Resistance to radioactivity • Not moisture sensitive • Good chemical resistance to acids, bases, oxidising agents	HF LFH RoHS
Polyethylene	PE	-40 °C to +50 °C	Black (BK), Grey (GY)	UL 94 HB	• Low moisture absorption • Good chemical resistance to most acids, bases, alcohol, oils	HF RoHS
Polyolefin	PO	-40 °C to +90 °C	Black (BK)	UL 94 V0	• Low smoke emissions	HF LFH RoHS
Polypropylene	PP	-40 °C to +115 °C	Black (BK), Natural (NA)	UL 94 HB	• Floats in water • Moderate yield strength • Good chemical resistance to acids, bases and solvents	HF RoHS
Polypropylene, Ethylene Propylene Diene Terpolymer rubber free of Nitrosamine	PP, EPDM	-20 °C to +95 °C	Black (BK)	UL 94 HB	• Good resistance to high temperature • Good chemical and abrasion resistance	HF RoHS
Polypropylene with metal particles	PPMP	-40 °C to +115 °C	Blue (BU)	UL 94 HB	• Metal and X-Ray detectable • Heat resistant • Moderate yield strength • Good chemical resistance	RoHS
Polypropylene with metal particles	PPMP+	-40 °C to +85 °C	Blue (BU)	not flame-retardant	• High yield strength • Metal and X-Ray detectable	HF RoHS
Polyvinylchloride	PVC	-10 °C to +70 °C	Black (BK), Natural (NA)	UL 94 V0	• Low moisture absorption • Good chemical resistance to acids, bases, salts, alcohol, oils	RoHS
Stainless Steel, Stainless Steel	SS304, SS316	-80 °C to +538 °C	Natural (NA)	non-burning	• Corrosion resistant • Antimagnetic • Weather resistant • Chemical resistance • SS316 also resistant against seawater, salt spray and anorganic acids	HF LFH RoHS
Thermoplastic Polyurethane	TPU	-40 °C to +85 °C	Black (BK)	UL 94 HB	• High elasticity • Good chemical resistance to acids, bases and oxidising agents	HF RoHS

Tefzel® is a registered trademark of DuPont. General linguistic usage for cable ties made from raw material E/TFE is Tefzel®-Tie. In addition to Tefzel® from DuPont HellermannTyton also uses equivalent E/TFE raw material from other suppliers.

*These details are only guide values. They should not be regarded as an exhaustive material specification and are no substitute for suitability tests. Please see our datasheets for further details.

HF = Halogen Free

LFH = Limited Fire Hazard

RoHS = Restriction of Hazardous Substances

**Further colours available on request.



= Minimum Loop Tensile Strength
for Cable Ties (newton)

For more material information
please visit our website.