

Heat shrinkable tubing 2:1 - flexible and coloured

TF21

PART DESCRIPTION	Supplied Ø D min.	Size (imperial)	Recov. Ø d max.	Wall (WT)
TF21-3.2/1.6-PO-X-YE	3.2	1/8 "	1.6	0.51
TF21-3.2/1.6-PO-X-BK	3.2	1/8 "	1.6	0.51
TF21-4.8/2.4-PO-X-BU	4.8	3/16 "	2.4	0.51
TF21-4.8/2.4-PO-X-RD	4.8	3/16 "	2.4	0.51
TF21-4.8/2.4-PO-X-WH	4.8	3/16 "	2.4	0.51
TF21-4.8/2.4-PO-X-YE	4.8	3/16 "	2.4	0.51
TF21-4.8/2.4-PO-X-OG	4.8	3/16 "	2.4	0.51
TF21-4.8/2.4-PO-X-BK	4.8	3/16 "	2.4	0.51
TF21-6.4/3.2-PO-X-BU	6.4	1/4 "	3.2	0.64
TF21-6.4/3.2-PO-X-RD	6.4	1/4 "	3.2	0.64
TF21-6.4/3.2-PO-X-WH	6.4	1/4 "	3.2	0.64
TF21-6.4/3.2-PO-X-YE	6.4	1/4 "	3.2	0.64
TF21-6.4/3.2-PO-X-BK	6.4	1/4 "	3.2	0.64
TF21-9.5/4.8-PO-X-BU	9.5	3/8 "	4.8	0.64
TF21-9.5/4.8-PO-X-OG	9.5	3/8 "	4.8	0.64
TF21-9.5/4.8-PO-X-RD	9.5	3/8 "	4.8	0.64
TF21-9.5/4.8-PO-X-WH	9.5	3/8 "	4.8	0.64
TF21-9.5/4.8-PO-X-YE	9.5	3/8 "	4.8	0.64
TF21-9.5/4.8-PO-X-BK	9.5	3/8 "	4.8	0.64
TF21-12.7/6.4-PO-X-BU	12.7	1/2 "	6.4	0.64
TF21-12.7/6.4-PO-X-RD	12.7	1/2 "	6.4	0.64
TF21-12.7/6.4-PO-X-WH	12.7	1/2 "	6.4	0.64
TF21-12.7/6.4-PO-X-YE	12.7	1/2 "	6.4	0.64
TF21-12.7/6.4-PO-X-BK	12.7	1/2 "	6.4	0.64
TF21-19.1/9.5-PO-X-OG	19.1	3/4 "	9.5	0.76
TF21-19.1/9.5-PO-X-BK	19.1	3/4 "	9.5	0.76
TF21-19.1/9.5-PO-X-BU	19.1	3/4 "	9.5	0.76
TF21-19.1/9.5-PO-X-RD	19.1	3/4 "	9.5	0.76
TF21-19.1/9.5-PO-X-WH	19.1	3/4 "	9.5	0.76
TF21-19.1/9.5-PO-X-YE	19.1	3/4 "	9.5	0.76
TF21-25.4/12.7-PO-X-BK	25.4	1 "	12.7	0.89
TF21-25.4/12.7-PO-X-BU	25.4	1 "	12.7	0.89
TF21-25.4/12.7-PO-X-RD	25.4	1 "	12.7	0.89
TF21-25.4/12.7-PO-X-WH	25.4	1 "	12.7	0.89
TF21-25.4/12.7-PO-X-YE	25.4	1 "	12.7	0.89
TF21-38.0/19.0-PO-X-BK	38.1	1-1/2 "	19.1	1.02
TF21-38.0/19.0-PO-X-BU	38.1	1-1/2 "	19.1	1.02
TF21-38.0/19.0-PO-X-RD	38.1	1-1/2 "	19.1	1.02
TF21-38.0/19.0-PO-X-WH	38.1	1-1/2 "	19.1	1.02
TF21-38.0/19.0-PO-X-YE	38.1	1-1/2 "	19.1	1.02
TF21-50.8/25.4-PO-X-BK	50.8	2 "	25.4	1.14
TF21-50.8/25.4-PO-X-BU	50.8	2 "	25.4	1.14

All dimensions in mm. Subject to technical changes.





Heat shrinkable tubing 2:1 - flexible and coloured

TF21



Heat Shrinkable Tubing 2:1

PART DESCRIPTION	Supplied Ø D min.	Size (imperial)	Recov. Ø d max.	Wall (WT)
TF21-50.8/25.4-PO-X-RD	50.8	2 "	25.4	1.14
TF21-50.8/25.4-PO-X-WH	50.8	2 "	25.4	1.14
TF21-50.8/25.4-PO-X-YE	50.8	2 "	25.4	1.14
TF21-76.0/38.0-PO-X-BK	76.2	3 "	38.1	1.27
TF21-76.0/38.0-PO-X-BU	76.2	3 "	38.1	1.27
TF21-76.0/38.0-PO-X-RD	76.2	3 "	38.1	1.27
TF21-76.0/38.0-PO-X-WH	76.2	3 "	38.1	1.27
TF21-76.0/38.0-PO-X-YE	76.2	3 "	38.1	1.27
TF21-101.6/50.8-PO-X-BK	101.6	4 "	50.8	1.40
TF21-101.6/50.8-PO-X-BU	101.6	4 "	50.8	1.40
TF21-101.6/50.8-PO-X-RD	101.6	4 "	50.8	1.40
TF21-101.6/50.8-PO-X-WH	101.6	4 "	50.8	1.40
TF21-101.6/50.8-PO-X-YE	101.6	4 "	50.8	1.40

All dimensions in mm. Subject to technical changes.