

DS-1PTSM3LCUL | DS-1PTSM4LCUL | DS-1PTSM3SCUL | DS-1PTSM4SCUL
Fiber Optic Pigtail, Multimode

Key Feature

- Excellent performance and durability in harsh field environments.
- LSZH, environmentally friendly and safer to use.
- OM3 or OM4.
- Compliant with RoHS 2.0.



Specification

Product Type	Fiber Optic Pigtail, Multimode				
General Specifications	Model	DS-1PTSM3LCUL	DS-1PTSM4LCUL	DS-1PTSM3SCUL	DS-1PTSM4SCUL
	Interface	LC/UPC	LC/UPC	SC/UPC	SC/UPC
	Body Style	Simplex	Simplex	Simplex	Simplex
	Connector Color	Aqua	Violet	Aqua	Violet
	Jacket Color	Aqua	Violet	Aqua	Violet
	Standard	IEC 61754-20-2002	IEC61754-20-2002	IEC 61754-4-2002	IEC 61754-20-2002
Optical Specifications	Fiber Mode	Multimode	Multimode	Multimode	Multimode
	Fiber Type	OM3	OM4	OM3	OM4
	Insertion Loss, maximum	0.20 dB			
	Return Loss, minimum	25 dB			
Dimensions	Length	1 m			
Mechanical Specifications	Bending Radius	20D(Dynamic), 10D(Static)			
	Durability	> 500 times			
Environmental Specifications	Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)			
Packaging and Weight	Packaging Quantity	1			
	Packaging Type	Bag			
Regulatory Compliance/Certifications	ROHS 2.0	Compliant			

Available Model

DS-1PTSM3LCUL (O-STD)

DS-1PTSM4LCUL (O-STD)

DS-1PTSM3SCUL(O-STD)

DS-1PTSM4SCUL(O-STD)

See Far, Go Further



www.hikvision.com
support@hikvision.com

