

Questo sito utilizza cookies per memorizzare informazioni sul tuo dispositivo I cookies aiutano il nostro sito a funzionare normalmente e ci mostrano come possiamo migliorare la tua esperienza come utente. Per continuare a navigare dovrai accettare la nostra [cookie policy](#) e la [normativa sulla privacy](#).

HIKVISION®

Authorized Distributors |  Italy-IT | Nazione/Area

HOME | PRODOTTI | SOLUZIONI | VMS | ROBOTICS | EZVIZ | FORMAZIONE & SUPPORTO | NEWS & EVENTI | PARTNERS | CHI S

Home > Prodotti > DVR > Serie 72 > 3MP

Cerca

Prodotti

Telecamere IP
Telecamere Analogiche
PTZ IP
PTZ Analogiche
Termiche
NVR
DVR
Serie 71
Serie 72 AcuSense
Serie 72
Serie 73 AcuSense
Serie 73
Serie 76
Serie 81
Serie 90
Serie 90 DeepinMind

HVR
Encoder
Mobile & Traffic
Storage di rete
Traffic
Alarm
Intercom
Controllo Accessi
Storage
Face Recognition Server
Accessori e Componenti
Transmission & Display
HIWATCH



DS-7204HQHI-K1/P/A New

Turbo HD DVR

PoC

Turbo HD DVR

Support H.265 Pro+/H.265 Pro/H.265 video compressi
Support HDTV/HD-CVI/CVBS/IP video input
Max. 6/12/24 IP cameras input (up to 6 MP)
Max. 800 m for 1080p and 1200 m for 720p HDTV i sig transmission
Up to 10 TB capacity per HDD

[Specifiche](#) | [Supporto Online](#)

DS-7204HQHI-K1/P/A

Video/Audio Input

Audio Input:	1-ch
Video Compression:	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Analog and HD-TVI video input:	4-ch, BNC interface (1.0Vp-p, 75 Ω) connection
Supported camera types:	4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25 Note: The 3 MP signal input is only available for channel 1 of DS-7204HQHI-K1, for channel 1/2of DS-7208HQHI-K1, and for channel 1/2/3/4 of DS-7216HQHI-K1. Support AHD input: 4 MP, 1080p25, 1080p30, 720p25, 720p30 Support CVI input: 1080p25, 1080p30, 720p25, 720p30 Support CVBS input
Video Input Interface:	BNC (1.0 Vp-p, 75Ω)
Audio Compression:	G.711u
Audio Input Interface:	RCA (2.0 Vp-p, 1 kΩ)
Two-way Audio:	1-ch, RCA (2.0 Vp-p, 1 kΩ) (using the 1st channel of audio input)

Video/Audio Output

HDMI/VGA Output:	1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz
Recording resolution:	When 1080p Lite mode not enabled: 4 MP lite/3 MP/1080p/1080p lite/720p/WD1/4CIF/VGA/CIF When 1080p Lite mode enabled: 4 MP lite/3 MP/1080p lite/720p/720p lite/WD1/4CIF/VGA/CIF
Frame Rate:	Main stream: When 1080p Lite mode not enabled: For 4 MP stream access: 4 MP lite@15fps; 1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) For 3 MP stream access: 3 MP/1080p/720p/VGA/WD1/4CIF/CIF@15fps For 1080p stream access: 1080p@15fps; 720p/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N) For 720p stream access: 720p/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N) When 1080p Lite mode enabled: 4 MP lite/3 MP@15fps; 1080p lite/720p/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N)
Video Bit Rate:	32 Kbps-6 Mbps
Stream Type:	Video/Video&Audio
Two-way Audio:	1-ch, RCA (2.0 Vp-p, 1 kΩ) (using the audio input)
Audio Output:	1-ch RCA(Linear, 1kΩ)

Audio Bit Rate:	64kbps
-----------------	--------

Dual Stream:	Support
--------------	---------

Synchronous Playback:	4-ch
-----------------------	------

Network management

Remote connections:	32
---------------------	----

Network protocols:	TCP/IP, PPPoE, DHCP, Hik-connect Cloud P2P,DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS,ONVIF
--------------------	--

Hard Disk Driver

Interface Type:	1 SATA Interface
-----------------	------------------

Capacity:	Up to 10 TB capacity for each disk
-----------	------------------------------------

External Interface

Network Interface:	1; 10M / 100M self-adaptive Ethernet interface
--------------------	--

USB Interface:	2 USB 2.0 Interfaces
----------------	----------------------

Serial Interface:	1; standard RS-485 serial interface, half-duplex
-------------------	--

Alarm Input:	4-ch
--------------	------

Alarm Output:	1-ch
---------------	------

General

Power Supply:	12V DC
---------------	--------

Consumption:	≤ 6W(without hard disks)
--------------	--------------------------

Working Temperature:	-10 oC to +55 oC (14 oF to 131 oF)
----------------------	------------------------------------

Working Humidity:	10% to 90%
-------------------	------------

Dimensions:	315 × 242 × 45 mm (12.4 × 9.5 × 1.8 inch)
-------------	---

Weight:	≤ 1.16 kg (2.6 lb)
---------	--------------------

Partners

Partner Tecnologici
Distributori
Embedded Open Platform

Support

Avvisi
Download
White Papers
Centro di sicurezza
Gestione Distributori
Cookie Policy
Privacy Policy

Altro

Richiesta informazioni
Contattaci
Iscrizione alla Newsletter

