

MINI DOME ANALOGICHE TURBO HD

720P

720P EXiR

720P Varifocal

1080P

1080P EXiR

1080P Varifocal


Modello	DS-2CE56C0T-IRMF	DS-2CE56C0T-IT3F	DS-2CE56C0T-VFIR3F	DS-2CE56D0T-IRMF	DS-2CE56D0T-IT3F	DS-2CE56D0T-VFIR3F
Sensore	1MP CMOS	1MP CMOS	1MP CMOS	2MP CMOS	2MP CMOS	2MP CMOS
Tecnologia	4 in 1 - TVI/AHD/CVI/CVBS selezionabili	4 in 1 - TVI/AHD/CVI/CVBS selezionabili	4 in 1 - TVI/AHD/CVI/CVBS selezionabili	4 in 1 - TVI/AHD/CVI/CVBS selezionabili	4 in 1 - TVI/AHD/CVI/CVBS selezionabili	4 in 1 - TVI/AHD/CVI/CVBS selezionabili
Pixel Effettivi	1296 x 732	1296 x 732	1296 x 732	1920 x 1080	1920 x 1080	1920 x 1080
Risoluzione	720P	720P	720P	1080P	1080P	1080P
Sensibilità	0.1 Lux @ F1.2, AGC ON 0 Lux con IR	0.1 Lux @ F1.2, AGC ON 0 Lux con IR	0.1 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR
Day & Night	ICR	ICR	ICR	ICR	ICR	ICR
Obiettivo	2.8 mm @ F1.2 3.6 mm opzionale	2.8 mm @ F1.2 3.6 mm opzionale 6 mm opzionale	2.8-12 mm @ F1.2 Varifocal	2.8 mm @ F1.2 3.6 mm opzionale 6 mm opzionale	3.6 mm @ F1.2 6 mm opzionale	2.8-12 mm @ F1.4 Varifocal
Velocità Shutter	1/25 s - 1/50.000 s	1/25 s - 1/50.000 s	1/25 s - 1/50.000 s	1/25 s - 1/50.000 s	1/25 s - 1/50.000 s	1/25 s - 1/50.000 s
BLC/DNR/HLC	No/Si/No	No/Si/No	No/Si/No	No/Si/No	No/Si/No	No/Si/No
Uscite Video	1 HD-TVI	1 HD-TVI	1 HD-TVI	1 HD-TVI	1 HD-TVI	1 HD-TVI
Portata IR	20 m Smart IR	40 m Smart IR Exir	40 m Smart IR	20 m Smart IR	40 m Smart IR Exir	40 m Smart IR
WDR	No	No	No	No	No	No
Dati	Up to Coax	Up to Coax	Up to Coax	Up to Coax	Up to Coax	Up to Coax
Alimentazione	12 VDC, 4W	12 VDC, 4W	12 VDC, 4W	12 VDC, 4W	12 VDC, 4W	12 VDC, 4W
Temperatura d'Esercizio	-40°C/+ 60°C, da esterno IP66	-40°C/+ 60°C, da esterno IP66	-40°C/+ 60°C, da esterno IP66	-40°C/+ 60°C, da esterno IP66	-40°C/+ 60°C, da esterno IP66	-40°C/+ 60°C, da esterno IP66