

TELECAMERE TURBO HD PoC 2MP Hik-Connect Cloud P2P



EXiR 2.0



EXiR 2.0

Varifocal



Varifocal



Modello	DS-2CE56D0T-IT1E	DS-2CE56D0T-IT3E	DS-2CE56D0T-VFIR3E	DS-2CE56D0T-VPiR3E
Risoluzione	2MP	2MP	2MP	2MP
Sensore	High-performance CMOS	High-performance CMOS	High-performance CMOS	High-performance CMOS
Pixel Effettivi	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080
Sensibilità	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR
Day & Night	ICR	ICR	ICR	ICR
Obiettivo	2.8 mm 3.6 mm opzionale	3.6 mm 6 mm opzionale	2.8-12 mm Varifocal	2.8-12 mm Varifocal
Velocità Shutter	1/25 s - 1/50.000 s			
BLC/DNR/HLC	No/Si/No	No/Si/No	No/Si/No	No/Si/No
Uscite Video	1 HD-TVI	1 HD-TVI	1 HD-TVI	1 HD-TVI
Portata IR	20 m Exir 2.0 Smart IR	40 m Exir 2.0 Smart IR	40 m	40 m
OSD	No	No	No	No
WDR	Digitale	Digitale	Digitale	Digitale
Dati	Up to Coax	Up to Coax	Up to Coax	Up to Coax
Alimentazione	12 VDC 4W max, PoC.af	12 VDC 4W max, PoC.af	12 VDC 6,5W max, PoC.at	12 VDC 4W max, PoC.af
Temperatura d'Esercizio	-40°C/+ 60°C, da esterno IP66	-40°C/+ 60°C, da esterno IP66	-40°C/+ 60°C, da esterno IP66	-40°C/+ 60°C, da esterno IP66, antivandalo IK10

Codice SAP	300609468 (2.8 mm) 300609469 (3.6 mm)	300609431 (3.6 mm) 300609327 (6 mm)	300610207	300610205
------------	--	--	-----------	-----------