

TELECAMERE EASY IP 2.0

2MP Hik-Connect
Cloud P2P

HiWATCH
HIKVISION



EXIR



Modello	DS-2CD2022WD-I	DS-2CD2T22WD-I5	DS-2CD2622FWD-I
Risoluzione	2MP (1920 X 1080)	2MP (1920 X 1080)	2MP (1920 X 1080)
Frame Rate	25 fps (1920 x 1080)	25 fps (1920 x 1080)	25 fps (1920 x 1080)
Sensore	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS
Sensibilità	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR
Day & Night	ICR	ICR	ICR
Obiettivo	4 mm 6 mm	4 mm 6 mm 12 mm	2.8-12 mm Varifocal
Compressione Video	H.264+/H.264	H.264+/H.264	H.264+/H.264
 smart Features	Line Crossing Detection, Intrusion Detection, Face Detection, Rol	Line Crossing Detection, Intrusion Detection, Face Detection, Rol	Line Crossing Detection, Intrusion Detection, Face Detection, Rol
Streams	2	2	2
Portata IR	30 m	50 m Exir Smart IR	30 m
Slot SD Card	-	-	1 microSD/SDHC/SDXC 128GB (non fornita)
WDR	120dB	120dB	120dB
Ingressi/Uscite Audio	-/-	-/-	-/-
Ingressi/Uscite Allarme	-/-	-/-	-/-
Alimentazione	12 VDC PoE 5W max	12 VDC PoE 7,5W max	12 VDC PoE 7,5W max
Temperatura d'Esercizio	-30°C/+ 60°C, da esterno IP67	-30°C/+ 60°C, da esterno IP67	-30°C/+ 60°C, da esterno IP67

Codice SAP	300710218 (4 mm) 300710399 (6 mm)	300710542 (4 mm) 300710550 (6 mm) 300710554 (12 mm)	300722345
------------	--------------------------------------	---	-----------