



Modello	DS-2CD2052-I	DS-2CD2T52-IS	DS-2CD2652F-I
Risoluzione	5MP (2560 x 1920)	5MP (2560 x 1920)	5MP (2560 x 1920)
Frame Rate	20 fps (2560 x 1920)	20 fps (2560 x 1920)	20 fps (2560 x 1920)
Sensore	1/3" Progressive Scan CMOS	1/3" Progressive Scan CMOS	1/3" Progressive Scan CMOS
Sensibilità	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR
Day & Night	ICR	ICR	ICR
Obiettivo	4 mm 6 mm	4 mm, 6 mm 12 mm opzionale	2.8-12 mm Varifocal
Compressione Video	H.264+/H.264	H.264+/H.264	H.264+/H.264
 Smart Features	Line Crossing Detection, Intrusion Detection, Face Detection, Rol	Line Crossing Detection, Intrusion Detection, Face Detection, Rol	Line Crossing Detection, Intrusion Detection, Face Detection, Rol
Streams	2	2	2
Portata IR	30 m	50 m Exir Smart IR	30 m
Slot SD Card	-	-	1 microSD/SDHC/SDXC 128GB (non fornita)
WDR	Digitale	Digitale	Digitale
Ingressi/Uscite Audio	-/-	-/-	-/-
Ingressi/Uscite Allarme	-/-	-/-	-/-
Alimentazione	12 VDC PoE 5,5W max	12 VDC PoE 7,5W max	12 VDC PoE 5,5W max
Temperatura d'Esercizio	-30°C/+ 60°C, da esterno IP66	-30°C/+ 60°C, da esterno IP66	-30°C/+ 60°C, da esterno IP66

Codice SAP	300718578 (4 mm) 300719673 (6 mm)	300719761 (4 mm) 300719762 (6 mm) 300719764 (12 mm)	300718531
------------	--------------------------------------	---	-----------