

Varifocal [Motorizzata]



Modello	DS-2CD2322WD-I	DS-2CD2122FWD-I	DS-2CD2722FWD-I [-I2S]	DS-2CD2422FWD-IW	DS-2CD2F22FWD-I	DS-2CD2522FWD-IS
Risoluzione	2MP (1920 x 1080)	2MP (1920 x 1080)	2MP (1920 x 1080)	2MP (1920 x 1080)	2MP (1920 x 1080)	2MP (1920 X 1080)
Frame Rate	25 fps (1920 x 1080)	25 fps (1920 x 1080)	25 fps (1920 x 1080)	25 fps (1920 x 1080)	25 fps (1920 x 1080)	25 fps (1920 x 1080)
Sensore	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS	1/2.7" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS
Sensibilità	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON, 0 Lux con IR	0.01 Lux @ F2.0, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR
Day & Night	ICR	ICR	ICR	ICR	ICR	ICR
Obiettivo	2.8 mm 4 mm 6 mm	2.8 mm 4 mm 6 mm	2.8-12 mm Varifocal [Varifocal Motorizzata]	2.8 mm 4 mm	4 mm 2.8 mm opzionale	2.8 mm
Compressione Video	H.264+/H.264	H.264+/H.264	H.264+/H.264	H.264+/H.264	H.264+/H.264	H.264+/H.264
 Smart Features	Line Crossing Detection, Intrusion Detection, Face Detection, Rol	Line Crossing Detection, Intrusion Detection, Face Detection, Rol	Line Crossing Detection, Intrusion Detection, Face Detection, Rol	Line Crossing Detection, Intrusion Detection, Face Detection, Rol	Line Crossing Detection, Intrusion Detection, Face Detection, Rol	Line Crossing Detection, Intrusion Detection, Face Detection, Rol
Streams	2	2	2	2	2	2
Portata IR	30 m Exir Smart IR	30 m	30 m	10 m	10 m	10 m
Slot SD Card	-	1 microSD/SDHC/SDXC 128GB (non fornita)	1 microSD/SDHC/SDXC 128GB (non fornita)	1 microSD/SDHC/SDXC 128GB (non fornita)	1 microSD/SDHC/SDXC 128GB (non fornita)	1 microSD/SDHC/SDXC 128GB (non fornita)
WDR	120dB	120dB	120dB	120dB	120dB	120dB
Ingressi/Uscite Audio	-/-	-/-	-/-	Microfono e Speaker incorporati	-/-	Microfono incorporato/1
Ingressi/Uscite Allarme	-/-	-/-	-/-	1/1 + sensore PIR (8 m)	-/-	1/1
Alimentazione	12 VDC PoE 7.5W max	12 VDC PoE 5W max	12 VDC PoE 5.5W max	12 VDC PoE 5W max	12VDC PoE 9W max	12 VDC PoE 5W max
Temperatura d'Esercizio	-30°C/+ 60°C, da esterno IP67	-30°C/+ 60°C, da esterno IP67, antivandalo IK10	-30°C/+ 60°C, da esterno IP67, antivandalo IK10	-10°C/+ 40°C	-10°C/+ 40°C	-30°C/+ 60°C, da esterno IP67, antivandalo IK08

Codice SAP	300807998 (2.8 mm) 300808075 (4 mm) 300808078 (6 mm)	300814826 (2.8 mm) 300808648 (4 mm) 300808642 (6 mm)	300808428 [-I] 300808438 [-I2S]	300721182 (2.8 mm) 300721269 (4 mm)	300808705 (2.8 mm) 300808709 (4 mm)	300813991
------------	--	--	------------------------------------	--	--	-----------