

TELECAMERE EASY IP 2.0

5MP Hik-Connect
Cloud P2P

HiWATCH
HIKVISION

Varifocal Motorizzata



Modello	DS-2CD2752F-IZS	DS-2CD2452F-IW	DS-2CD2552F-I
Risoluzione	5MP (2560 x 1920)	5MP (2560 x 1920)	5MP (2560 x 1920)
Frame Rate	20 fps (2560 x 1920)	20 fps (2560 x 1920)	20 fps (2560 x 1920)
Sensore	1/3" Progressive Scan CMOS	1/3.2" Progressive Scan CMOS	1/3" Progressive Scan CMOS
Sensibilità	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR
Day & Night	ICR	ICR	ICR
Obiettivo	2.8-12 mm Varifocal Motorizzata	2.8 mm 4 mm	4 mm
Compressione Video	H.264+/H.264	H.264+/H.264	H.264+/H.264
 smart Features	Line Crossing Detection, Intrusion Detection, Face Detection, Rol	Line Crossing Detection, Intrusion Detection, Face Detection, Rol	Line Crossing Detection, Intrusion Detection, Face Detection, Rol
Streams	2	2	2
Portata IR	30 m	10 m	10 m
Slot SD Card	1 microSD/SDHC/SDXC 128GB (non fornita)	1 microSD/SDHC/SDXC 128GB (non fornita)	1 microSD/SDHC/SDXC 128GB (non fornita)
WDR	Digitale	Digitale	Digitale
Ingressi/Uscite Audio	1/1	Microfono e Speaker incorporati	-/-
Ingressi/Uscite Allarme	1/1	1/1 + sensore PIR (8 m)	-/-
Alimentazione	12 VDC PoE 5,5W max	12 VDC PoE 5W max	12 VDC PoE 5W max
Temperatura d'Esercizio	-30°C/+ 60°C, da esterno IP67, antivandalo IK10	-10°C/+ 40°C	-30°C/+ 60°C, da esterno IP66, antivandalo IK08
Codice SAP	300814511	300721373 (2.8 mm) 300724197 (4 mm)	300815032