

TELECAMERE EASY IP 1.0

2MP Hik-Connect
Cloud P2P

HiWATCH
HIKVISION

Varifocal Motorizzata



Varifocal Motorizzata

Varifocal Motorizzata

Modello	DS-2CD1021-I	DS-2CD1621FWD-IZ	DS-2CD1321-I	DS-2CD1H21WD-IZ	DS-2CD1721FWD-IZ
Risoluzione	2MP (1920 X 1080)	2MP (1920 X 1080)	2MP (1920 X 1080)	2MP (1920 X 1080)	2MP (1920 X 1080)
Frame Rate	25 fps (1920 x 1080)	25 fps (1920 x 1080)	25 fps (1920 x 1080)	25 fps (1920 x 1080)	25 fps (1920 x 1080)
Sensore	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS
Sensibilità	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR
Day & Night	ICR	ICR	ICR	ICR	ICR
Obiettivo	4 mm 2.8 mm opzionale	2.8-12mm Varifocal Motorizzata	2.8 mm 4 mm	2.8-12 mm Varifocal Motorizzata	2.8-12 mm Varifocal Motorizzata
Compressione Video	H.264+/H.264	H.264+/H.264	H.264+/H.264	H.264+/H.264	H.264+/H.264
	-	-	-	-	-
Streams	2	2	2	2	2
Portata IR	30 m	30 m	30 m	30 m	30 m
Slot SD Card	-	1 Micro SD/SDHC/SDXC 128GB (non fornita)	-	-	1 Micro SD/SDHC/SDXC 128GB (non fornita)
WDR	Digitale	120 dB	Digitale	120dB	120dB
Ingressi/Uscite Audio	-/-	-/-	-/-	-/-	-/-
Ingressi/Uscite Allarme	-/-	-/-	-/-	-/-	-/-
Alimentazione	12 VDC PoE 6W max	12 VDC PoE 11W max	12 VDC PoE 6W max	12 VDC PoE 11W max	12 VDC PoE 11W max
Temperatura d'Esercizio	-30 °C/+ 60 °C, da esterno IP 67	-30 °C/+ 60 °C, da esterno IP 67	-30 °C/+ 60 °C, da esterno IP 67	-30 °C/+ 60 °C, da esterno IP 67	-30 °C/+ 60 °C, da esterno IP67, antivandalo IK10

Codice SAP	300726785 (2.8 mm) 300726797 (4 mm)	300726257	300820158 (2.8 mm) 300820486 (4 mm)	300820086	300820278
------------	--	-----------	--	-----------	-----------