

Varifocal [Motorizzata]



|  |   |   |   |   |   |   |
|--|---|---|---|---|---|---|
| Modello  | DS-2CD2322WD-I  | DS-2CD2122FWD-I   | DS-2CD2722FWD-I [-I-ZS]   | DS-2CD2422FWD-IW  | DS-2CD2F22FWD-I   | DS-2CD2522FWD-IS  |
| Risoluzione  | 2MP (1920 x 1080)   |
| Frame Rate   | 25 fps (1920 x 1080)  |
| Sensore  | 1/2.8" Progressive Scan CMOS  | 1/2.8" Progressive Scan CMOS  | 1/2.8" Progressive Scan CMOS  | 1/2.7" Progressive Scan CMOS  | 1/2.8" Progressive Scan CMOS  | 1/2.8" Progressive Scan CMOS  |
| Sensibilità  | 0.01 Lux @ F1.2, AGC ON<br>0 Lux con IR                                 | 0.01 Lux @ F1.2, AGC ON<br>0 Lux con IR                                 | 0.01 Lux @ F1.2, AGC ON<br>0 Lux con IR                                 | 0.01 Lux @ F1.2, AGC ON,<br>0 Lux con IR                                | 0.01 Lux @ F2.0, AGC ON<br>0 Lux con IR                                 | 0.01 Lux @ F1.2, AGC ON<br>0 Lux con IR                                 |
| Day & Night  | ICR   | ICR   | ICR   | ICR   | ICR   | ICR   |
| Obiettivo  | 2.8 mm<br>4 mm<br>6 mm  | 2.8 mm<br>4 mm<br>6 mm  | 2.8-12 mm Varifocal<br>[Varifocal Motorizzata]                          | 2.8 mm<br>4 mm  | 4 mm<br>2.8 mm opzionale  | 2.8 mm  |
| Compressione Video   | H.264+/H.264  | H.264+/H.264  | H.264+/H.264  | H.264+/H.264  | H.264+/H.264  | H.264+/H.264  |
|  smart<br>Features | Line Crossing Detection,<br>Intrusion Detection,<br>Face Detection, Rol |
| Streams  | 2   | 2   | 2   | 2   | 2   | 2   |
| Portata IR   | 30 m Exir Smart IR  | 30 m  | 30 m  | 10 m  | 10 m  | 10 m  |
| Slot SD Card   | -   | 1 microSD/SDHC/SDXC 128GB<br>(non fornita)                              |
| WDR  | 120dB   | 120dB   | 120dB   | 120dB   | 120dB   | 120dB   |
| Ingressi/Uscite Audio  | -/-   | -/-   | -/-   | Microfono e Speaker incorporati   | -/-   | Microfono incorporato/1   |
| Ingressi/Uscite Allarme  | -/-   | -/-   | -/-   | 1/1 + sensore PIR (8 m)   | -/-   | 1/1   |
| Alimentazione  | 12 VDC PoE 7,5W max   | 12 VDC PoE 5W max   | 12 VDC PoE 5,5W max   | 12 VDC PoE 5W max   | 12VDC PoE 9W max  | 12 VDC PoE 5W max   |
| Temperatura d'Esercizio  | -30°C/+ 60°C, da esterno IP67   | -30°C/+ 60°C, da esterno IP67,<br>antivandalo IK10                      | -30°C/+ 60°C, da esterno IP67,<br>antivandalo IK10                      | -10°C/+ 40°C  | -10°C/+ 40°C  | -30°C/+ 60°C, da esterno IP67,<br>antivandalo IK08                      |

|            |  |  |                   |  |  |           |
|------------|--|--|-------------------|--|--|-----------|
| Codice SAP | 300807998 (2.8 mm)<br>300808075 (4 mm)<br>300808078 (6 mm) | 300814826 (2.8 mm)<br>300808648 (4 mm)<br>300808642 (6 mm) | 300808438 [-I-ZS] | 300721182 (2.8 mm)<br>300721269 (4 mm) | 300808705 (2.8 mm)<br>300808709 (4 mm) | 300813991 |
|------------|--|--|-------------------|--|--|-----------|