

# TELECAMERE EASY IP 2.0

4MP Hik-Connect Cloud P2P

HiWATCH  
HIKVISION



Varifocal



Varifocal



Varifocal Motorizzata



Modello	DS-2CD2042WD-I	DS-2CD2T42WD-I5	DS-2CD2642FWD-I	DS-2CD2342WD-I	DS-2CD2742FWD-I	DS-2CD2742FWD-IZS
Risoluzione	4MP (2688 x 1520)	4 MP (2688 x 1520)	4 MP (2688 x 1520)			
Frame Rate	20 fps (2688 x 1520)					
Sensore	1/3" Progressive Scan CMOS					
Sensibilità	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR
Day & Night	ICR	ICR	ICR	ICR	ICR	ICR
Obiettivo	6 mm	4 mm ,6 mm 12 mm opzionale	2.8-12 mm Varifocal	4 mm, 12 mm 2.8 mm, 6 mm opzionali	2.8-12 mm Varifocal	2.8-12 mm Varifocal Motorizzata
Compressione Video	H.264+/H.264	H.264+/H.264	H.264+/H.264	H.264+/H.264	H.264+/H.264	H.264+/H.264
 Smart Features	Line Crossing Detection, Intrusion Detection, Face Detection, Rol					
Streams	2	2	2	2	2	2
Portata IR	30 m	50 m Exir Smart IR	30 m	30 m	30 m	30 m
Slot SD Card	-	-	1 microSD/SDHC/SDXC 128GB (non fornita)	-	1 microSD/SDHC/SDXC 128GB (non fornita)	1 microSD/SDHC/SDXC 128GB (non fornita)
WDR	120dB	120dB	120dB	120dB	120dB	120dB
Ingressi/Uscite Audio	-/-	-/-	-/-	-/-	-/-	1/1
Ingressi/Uscite Allarme	-/-	-/-	-/-	-/-	-/-	1/1
Alimentazione	12 VDC PoE 5W max	12 VDC PoE 7,5W max	12 VDC PoE 7,5W max	12 VDC PoE 7,5W max	12 VDC PoE 5,5W max	12 VDC PoE 5,5W max
Temperatura d'Esercizio	-30°C/+ 60°C, da esterno IP67	-30°C/+ 60°C, da esterno IP67, antivandalato IK10	-30°C/+ 60°C, da esterno IP67, antivandalato IK10			

Codice SAP	300710414	300710586 (4 mm) 300710588 (6 mm) 300710591 (12 mm)	300710952	300807999 (2.8 mm) 300808085 (4 mm) 300808090 (6 mm) 300808095 (12 mm)	300808349	300808366
------------	-----------	---	-----------	---	-----------	-----------

\* Disponibile esclusivamente su richiesta