

TELECAMERE EASY IP 2.0

4MP Hik-Connect
Cloud P2P



Fisheye 180°



Modello	DS-2CD2442FWD-IW	DS-2CD2F42FWD-I	DS-2CD2542FWD-IS	DS-2CD2942F-I
Risoluzione	4 MP (2688 x 1520)	4 MP (2688 x 1520)	4MP (2688 x 1520)	4MP (2560 x 1440)
Frame Rate	20 fps (2688 x 1520)	20 fps (2688 x 1520)	20 fps (2688 x 1520)	12.5 fps (2560 x 1440)
Sensore	1/2.8" Progressive Scan CMOS	1/3" Progressive Scan CMOS	1/3" Progressive Scan CMOS	1/3" Progressive Scan CMOS
Sensibilità	0.01 Lux @ F1.2, AGC ON, 0 Lux con IR	0.01 Lux @ F1.2, AGC ON, 0 Lux con IR	0.01 Lux @ F1.2, AGC ON, 0 Lux con IR	0.01 Lux @ F2.0, AGC ON 0 Lux con IR
Day & Night	ICR	ICR	ICR	ICR
Obiettivo	2.8 mm 4 mm	4 mm 2.8 mm opzionale	2.8 mm	1.6 mm
Compressione Video	H.264+/H.264	H.264+/H.264	H.264+/H.264	H.264+/H.264
 smart Features	Line Crossing Detection, Intrusion Detection, Face Detection, Rol	Line Crossing Detection, Intrusion Detection, Face Detection, Rol	Line Crossing Detection, Intrusion Detection, Face Detection, Rol	Line Crossing Detection, Intrusion Detection, Rol
Streams	2	2	2	2
Portata IR	10 m	10 m	10 m	8 m
Slot SD Card	1 microSD/SDHC/SDXC 128GB (non fornita)	1 microSD/SDHC/SDXC 128GB (non fornita)	1 microSD/SDHC/SDXC 128GB (non fornita)	1 microSD/SDHC/SDXC 128GB (non fornita)
WDR	120dB	120dB	120dB	Digitale
Ingressi/Uscite Audio	Microfono e Speaker incorporati	-/-	Microfono incorporato/1	-/-
Ingressi/Uscite Allarme	1/1 + sensore PIR (8 m)	-/-	1/1	-/-
Alimentazione	12 VDC PoE 5W max	12 VDC PoE 9W max	12 VDC PoE 5W max	12 VDC PoE 6W max
Temperatura d'Esercizio	-10°C/+ 40°C	-10°C/+ 40°C	-30°C/+ 60°C, da esterno IP67, antivandalo IK08	-10°C/+ 40°C

Codice SAP 300723525 (2.8 mm)
300721362 (4 mm)

300808745 (2.8 mm)
300808749 (4 mm)

300808148

300806714