

TELECAMERE EASY IP 2.0

5MP Hik-Connect
Cloud P2P



EXIR



Varifocal Motorizzata



Modello	DS-2CD2352-I	DS-2CD2152F-I	DS-2CD2752F-I
Risoluzione	5MP (2560 x 1920)	5MP (2560 x 1920)	5MP (2560 x 1920)
Frame Rate	20 fps (2560 x 1920)	20 fps (2560 x 1920)	20 fps (2560 x 1920)
Sensore	1/3" Progressive Scan CMOS	1/3" Progressive Scan CMOS	1/3" Progressive Scan CMOS
Sensibilità	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR	0.01 Lux @ F1.2, AGC ON 0 Lux con IR
Day & Night	ICR	ICR	ICR
Obiettivo	6 mm	4 mm 6 mm	2.8-12 mm Varifocal
Compressione Video	H.264+/H.264	H.264+/H.264	H.264+/H.264
 smart Features	Line Crossing Detection, Intrusion Detection, Face Detection, Rol	Line Crossing Detection, Intrusion Detection, Face Detection, Rol	Line Crossing Detection, Intrusion Detection, Face Detection, Rol
Streams	2	2	2
Portata IR	30 m Exir Smart IR	30 m	30 m
Slot SD Card	-	1 microSD/SDHC/SDXC 128GB (non fornita)	1 microSD/SDHC/SDXC 128GB (non fornita)
WDR	Digitale	Digitale	Digitale
Ingressi/Uscite Audio	-/-	-/-	-/-
Ingressi/Uscite Allarme	-/-	-/-	-/-
Alimentazione	12 VDC PoE 5,5W max	12 VDC PoE 5W max	12 VDC PoE 5,5W max
Temperatura d'Esercizio	-30°C/+ 60°C, da esterno IP66	-30°C/+ 60°C, da esterno IP67, antivandalo IK10	-30°C/+ 60°C, da esterno IP67, antivandalo IK10

Codice SAP 300815008

300815112 (4 mm)
300815113 (6 mm)

300814995