

# SPEED DOME IP MEGAPIXEL

2MP Hik-Connect  
Cloud P2P

4x



25x



25x



UltraLow  
Light

UltraLow  
Light

Modello	DS-2DE2204IW-DE3/W	DS-2DE5225W-AE	DS-2DE5225IW-AE
Risoluzione	2MP (1920 x 1080)	2MP (1920 x 1080)	2MP (1920 x 1080)
Sensore	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS
Frame Rate	25fps (1920 x 1080)	25fps (1920 x 1080)	25fps (1920 x 1080)
Sensibilità	Col.: 0.05 Lux @ F2.0 B/N: 0.005 Lux @ F2.0 0 Lux con IR	Col.: 0.005 Lux @ F1.6 B/N: 0.001 Lux @ F1.6	Col.: 0.005 Lux @ F1.6 B/N: 0.001 Lux @ F1.6 0 Lux con IR
Day & Night	ICR	ICR	ICR
Obiettivo	2.8 - 12 mm	4.8-120 mm	4.8-120 mm
Zoom Ottico/Zoom Digitale	4x/16x	25x/16x	25x/16x
Limite Pan/Tilt	Da 0° a 350° / Da 0° a 90°	360° Infinito / Da -5° a 90° (Auto Flip)	360° Infinito / Da -15° a 90° (Auto Flip)
Velocità Pan	Manuale: Da 0.1° a 60°/s	Manuale: Da 0.1° a 250°/s Preset: 300°/s	Manuale: Da 0.1° a 120°/s Preset: 120°/s
Velocità Tilt	Da 0.1° a 50°/s	Manuale: Da 0.1° a 150°/s Preset: 200°/s	Manuale: Da 0.1° a 80°/s Preset: 80°/s
Preset/Patrol/Pattern	300/8/4	300/8/4	300/8/4
Compressione Video	H.265+/H.265/H.264+/H.264	H.265+/H.265/H.264+/H.264	H.265+/H.265/H.264+/H.264
 smart Features	Line Crossing Detection, Intrusion Detection, Audio Exception Detection, Rol	Line Crossing Detection, Intrusion Detection, Region Entrance Detection, Unattended Baggage Detection, Face Detection, Rol	Line Crossing Detection, Intrusion Detection, Region Entrance Detection, Region Exiting Detection, Object Removal Detection, Unattended Baggage Detection, Face Detection, Rol
Preset/Patrol/Pattern	300/8/-	300/8/4	300/8/4
Streams	3	3	3
Portata IR	20m	-	150 m
Slot SD Card	1 Micro SD/SDHC/SDXC 128 GB (non fornita)	1 Micro SD/SDHC/SDXC 256 GB (non fornita)	1 Micro SD/SDHC/SDXC 256 GB (non fornita)
WDR	Digitale	120 dB	120 dB
Ingressi/Uscite	1/1 Audio 1/1 Allarme	-/- Audio -/- Allarme	-/- Audio -/- Allarme
Alimentazione	24 VAC, Hi-PoE 9W max	24 VAC, Hi-PoE 24W max	24 VAC, Hi-PoE 30W max
Temperatura d'Esercizio	-10 °C/+ 50 °C, da interno, da superficie	-30°C/+ 65°C, da esterno IP66, antivandalato IK10, pendant	-30°C/+ 65°C, da esterno IP66, pendant

Codice SAP 301308529

301312060

301312111