HIKVISION®

Authorised Distributors | 🇬🇧 - 🇮🇪 UK & Ireland | Region / Language   Login   Search

| HOME | PRODUCTS | SOLUTIONS | EZVIZ | ROBOTICS | VMS | NEWS & EVENTS | PARTNERS | LEARNING & SUPPORT | ABOUT HIKV |

#1 Worldwide
Video Surveillance Complete Solution Provide

Home > Products > Transmission & Display > Monitor   Search P

Products

- Network Cameras
- Thermal Cameras
- Analogue Cameras
- PTZ
- Network Video Recorders
- Digital Video Recorders
- Encoders & Decoders
- Video Encoder & Decoder Cards
- Video Intercoms
- Mobile
- Transmission & Display
  - LCD Large Screen
  - Decoder
  - Keyboard
  - Monitor
  - Controller
  - Network Switch
  - Accessory
  - Wireless Bridge
- Access Control
- Traffic
- Accessories
- Intelligent Storage
- Hiwatch

DS-D5019QE-B 🔴New

19" LED Monitor

LED backlit technology with HD 1366×768
Wide view angle: 90°(H)/65°(V)
3D comb filter
3D De-interlace
3D noise reduction
Input: HDMI, VGA
VESA stand bracket

Specification | Download | Online Support

DS-D5019QE-B

Display

Display Type:	LED-Backlit TFT LCD
Screen Size:	18.5"
Pixel Pitch(H×V):	0.300mm×0.300mm
Max Resolution:	1366×768
Brightness:	200cd/m2 (Typical)
Contrast:	600:1
Response Time:	5ms
Color:	16.7M
Viewing Angle:	Horizontal 90°, Vertical 65°

Input

HDMI:	1
VGA:	1

Mounting

VESA:	75mmx 75mm

General

Consumption:	< 20W(on) < 0.5W(Standby)
Power Supply:	AC100 ~ 240V, 50 /60Hz
Operation Temperature:	0°C ~ 40 °C
Operating Humidity:	10%~85% (No Condensation)
Storage Temperature:	-20°C ~ 60°C
Storage Humidity:	5%~95% (No Condensation)

Weight:	3.5Kg(Grossweight) , 2.8(Net weight)
Dimension (W×H×D):	445.58mm*274.99mm*44.6mm

Highlight	Partners	Support	Others	
2016 IHS Research Ranking	Disclaimer for Unauthorized Distributor	Cookie Policy	Online Inquiry	Global Operations
	VMS Partnership Standards	Privacy Policy	Contact Us	
		Security Centre		
		Download		
		White Paper		