

Questo sito utilizza cookies per memorizzare informazioni sul tuo dispositivo I cookies aiutano il nostro sito a funzionare normalmente e ci mostrano come possiamo migliorare la tua esperienza come utente. Per continuare a navigare dovrai accettare la nostra [cookie policy](#) e la [normativa sulla privacy](#).

# HIKVISION®

Authorized Distributors |  Italy-IT | Nazione/Area

HOME | PRODOTTI | SOLUZIONI | VMS | ROBOTICS | EZVIZ | FORMAZIONE & SUPPORTO | NEWS & EVENTI | PARTNERS | CHI S

Home > Prodotti > NVR > Serie 76 > Serie Q

Cerca

## Prodotti

- Telecamere IP
- Telecamere Analogiche
- PTZ IP
- PTZ Analogiche
- Termiche
- NVR
  - Serie 71
  - Serie 76 AcuSense
  - Serie 76
  - Serie 77 AcuSense
  - Serie 77
  - Serie 96
  - Serie 96 Videowall Management
  - Serie 96 DeepinMind
- DVR
- HVR
- Encoder
- Mobile & Traffic
- Storage di rete
- Traffic
- Alarm
- Intercom
- Controllo Accessi
- Storage
- Face Recognition Server
- Accessori e Componenti
- Transmission & Display
- HiWATCH



DS-7608NI-Q2/8P New

NVR

**8 PoE**

NVR

**HD Input**

H.265+/H.265/H.264/H.264+ video formats  
Connectable to the third-party network cameras  
Up to 16 IP cameras can be connected  
Recording at up to 8 MP resolution  
Supports live view, storage, and playback of the camera at up to 8 MP resolution

**HD Output**

HDMI and VGA independent outputs  
HDMI Video output at up to 4K (3840 × 2160) resolution

**HD Storage**

2 SATA interfaces connectable for recording and backup  
H.265+ compression effectively reduces the storage costs by up to 75%

**HD Transmission**

1 self-adaptive 10/100/1000 Mbps network interface  
8/16 independent PoE network interfaces are provided

**Various Applications**

Centralized management of IP cameras, including configuration information import/export, real-time information display, audio, upgrade, etc.  
Connectable to smart IP cameras from Hikvision and recording, playing back, and backing up of VCA alarm realized  
VCA detection alarm is supported  
Instant playback for assigned channel during multi-channel display mode  
Smart search for the selected area in the video; and smart playback to improve the playback efficiency  
Hik-Connect for easy network management

[Specifiche](#) | [Download](#) | [Supporto Online](#)

DS-7608NI-Q2/8P

### Video/Audio Input

IP video input:	8-ch
Two-way audio input:	1-ch, RCA (2.0 Vp-p, 1kΩ)
IP Video input:	Up to 8 MP resolution

### Network

Incoming bandwidth:	80Mbps
Outgoing bandwidth:	80Mbps

### Video/Audio Output

HDMI/VGA output:	HDMI: 1-ch, 4K (3840 × 2160)/30Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz VGA: 1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Recording Resolution:	8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Audio Output:	1-ch, RCA (Linear, 1kΩ)

### Decoding

Synchronous playback:	8-ch
Capability:	1-ch @ 8 MP / 4-ch @ 1080p
Live view / Playback:	8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF

### Decoding format

Decoding format :	H.265/H.265+/H.264/H.264+/MPEG4
-------------------	---------------------------------

### Hard Disk

SATA:	2 SATA interface
Capacity:	Up to 6TB capacity for each disk

### External Interface

Network Interface:	1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
USB Interface:	2, USB2.0

### POE

Max. Power:	80W
Interface:	8 independent 10 /100 Mbps PoE Ethernet interfaces

### General

Power Supply:	100 to 240 VAC
Power:	≤ 180W
Consumption(without hard disk and POE):	≤ 15W
Working Temperature:	-10 oC ~ +55 oC (+14 oF~ + 131 oF)
Working Humidity:	10 % ~ 90 %
Chassis:	1U chassis
Dimensions:	385 × 315 × 52 mm (15.2"× 12.4" × 2.0")
Weight(without HDD):	≤ 2.6 kg (5.7 lb)

#### Partners

Partner Tecnologici  
Distributori  
Embedded Open Platform

#### Support

Avvisi  
Download  
White Papers  
Centro di sicurezza  
Gestione Distributori  
Cookie Policy  
Privacy Policy

#### Altro

Richiesta informazioni  
Contattaci  
Iscrizione alla Newsletter

