

Questo sito utilizza cookies per memorizzare informazioni sul tuo dispositivo I cookies aiutano il nostro sito a funzionare normalmente e ci mostrano come possiamo migliorare la tua esperienza come utente. Per continuare a navigare dovrai accettare la nostra [cookie policy](#) e la [normativa sulla privacy](#).

HIKVISION®

Authorized Distributors |  Italy-IT | Nazione/Area

HOME | PRODOTTI | SOLUZIONI | VMS | ROBOTICS | EZVIZ | FORMAZIONE & SUPPORTO | NEWS & EVENTI | PARTNERS | CHI SIAMO

Home > Prodotti > NVR > Serie 76 > Serie Q

Cerca

Prodotti

- Telecamere IP
- Telecamere Analogiche
- PTZ IP
- PTZ Analogiche
- Termiche
- NVR
 - Serie 71
 - Serie 76 AcuSense
 - Serie 76
 - Serie 77 AcuSense
 - Serie 77
 - Serie 96
 - Serie 96 Videowall Management
 - Serie 96 DeepinMind
- DVR
- HVR
- Encoder
- Mobile & Traffic
- Storage di rete
- Traffic
- Alarm
- Intercom
- Controllo Accessi
- Storage
- Face Recognition Server
- Accessori e Componenti
- Transmission & Display
- HiWATCH



DS-7616NI-Q2/16P New

NVR

16 PoE

NVR

HD Input

H.265+/H.265/H.264/H.264+ video formats
Connectable to the third-party network cameras
Up to 16 IP cameras can be connected
Recording at up to 8 MP resolution
Supports live view, storage, and playback of the camera at up to 8 MP resolution

HD Output

HDMI and VGA independent outputs
HDMI Video output at up to 4K (3840 × 2160) resolution

HD Storage

2 SATA interfaces connectable for recording and backup
H.265+ compression effectively reduces the storage costs by up to 75%

HD Transmission

1 self-adaptive 10/100/1000 Mbps network interface
8/16 independent PoE network interfaces are provided

Various Applications

Centralized management of IP cameras, including configuration import/export, real-time information display, audio, upgrade, etc.
Connectable to smart IP cameras from Hikvision and recording, playing back, and backing up of VCA alarm realized
VCA detection alarm is supported
Instant playback for assigned channel during multi-channel display mode
Smart search for the selected area in the video; and playback to improve the playback efficiency
Hik-Connect for easy network management

[Specifiche](#) | [Download](#) | [Supporto Online](#)

DS-7616NI-Q2/16P

Video/Audio Input

IP video input:	16-ch
Two-way audio input:	1-ch, RCA (2.0 Vp-p, 1kΩ)
IP Video input:	Up to 8 MP resolution

Network

Incoming bandwidth:	160Mbps
Outgoing bandwidth:	80Mbps

Video/Audio Output

HDMI/VGA output:	HDMI: 1-ch, 4K (3840 × 2160)/30Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz VGA: 1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Recording Resolution:	8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Audio Output:	1-ch, RCA (Linear, 1kΩ)

Decoding

Synchronous playback: 16-ch

Capability: 1-ch @ 8 MP / 4-ch @ 1080p

Live view / Playback: 8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF

Decoding format

Decoding format : H.265/H.265+/H.264/H.264+/MPEG4

Hard Disk

SATA: 2 SATA interface

Capacity: Up to 6TB capacity for each disk

External Interface

Network Interface: 1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface

USB Interface: 2, USB2.0

POE

Interface: 16 independent 10/100 Mbps PoE Ethernet interfaces

General

Power Supply: 100 to 240 VAC

Power: ≤ 280W

Consumption(without hard disk and POE): ≤ 15W

Working Temperature: -10 oC ~ +55 oC (+14 oF~ + 131 oF)

Working Humidity: 10 % ~ 90 %

Chassis: 1U chassis

Dimensions: 385 × 315 × 52 mm (15.2"× 12.4" × 2.0")

Weight(without HDD): ≤ 2.6 kg (5.7 lb)

Partners

Partner Tecnologici
Distributori
Embedded Open Platform

Support

Avvisi
Download
White Papers
Centro di sicurezza
Gestione Distributori
Cookie Policy
Privacy Policy

Altro

Richiesta informazioni
Contattaci
Iscrizione alla Newsletter

