

Questo sito utilizza cookies per memorizzare informazioni sul tuo dispositivo I cookies aiutano il nostro sito a funzionare normalmente e ci mostrano come possiamo migliorare la tua esperienza come utente. Per continuare a navigare dovrai accettare la nostra [cookie policy](#) e la [normativa sulla privacy](#).

HIKVISION®

Authorized Distributors |  Italy-IT | Nazione/Area

HOME | PRODOTTI | SOLUZIONI | VMS | ROBOTICS | EZVIZ | FORMAZIONE & SUPPORTO | NEWS & EVENTI | PARTNERS | CHI S

Home > Prodotti > NVR > Serie 71 > Serie Q

Cerca

Prodotti

- Telecamere IP
- Telecamere Analogiche
- PTZ IP
- PTZ Analogiche
- Termiche
- NVR
 - Serie 71
 - Serie 76 AcuSense
 - Serie 76
 - Serie 77 AcuSense
 - Serie 77
 - Serie 96
 - Serie 96 Videowall Management
 - Serie 96 DeepinMind
- DVR
- HVR
- Encoder
- Mobile & Traffic
- Storage di rete
- Traffic
- Alarm
- Intercom
- Controllo Accessi
- Storage
- Face Recognition Server
- Accessori e Componenti
- Transmission & Display
- HiWATCH



DS-7104NI-Q1/4P

NVR

4 PoE

NVR

Video Input and Transmission

Connectable to the third-party network cameras
Up to 8 network cameras can be connected

Compression and Recording

H.265+/H.265 compression effectively reduces the storage space and costs
Full channel recording at up to 4 MP resolution

HD Video Output

HDMI/VGA output at 1080p resolution

Storage and Playback

1-ch playback at 4 MP resolution or 2-ch at 1080p resolution
1 SATA hard disk can be connected with 6TB capacity

Smart Function

Supports line crossing and intrusion detection
Smart search for the selected area in the video; and smart playback to improve the playback efficiency

Network & Ethernet Access

Hik-Connect for easy network management
100 Mbps Ethernet network interface
4/8 independent 100 Mbps built-in switch network interfaces

[Specifiche](#) | [Download](#) | [Supporto Online](#)

DS-7104NI-Q1/4P

Video/Audio Input

IP video input:	4-ch
IP Video input:	Up to 4 MP resolution

Network

Incoming bandwidth:	40Mbps
Outgoing bandwidth:	60 Mbps

Video/Audio Output

LCD/HDMI/VGA output resolution:	1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Recording Resolution:	4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF

Decoding

Decoding format:	H.265+/H.265/ H.264+/H.264
Synchronous playback:	4-ch
Capability:	1-ch @ 4 MP / 2-ch @ 1080p
Live view / Playback:	4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF

Hard Disk

SATA:	1 SATA interface
-------	------------------

Capacity: Up to 6TB capacity for each disk

External Interface

Network Interface: 1 RJ-45 10 / 100 Mbps selfadaptive Ethernet interface

USB Interface: 2, USB2.0

POE

Max. Power: 35W

Interface: 4 independent 100 Mbps PoE network interfaces

General

Power Supply: 48 VDC

Power: ≤ 50W

Consumption(without hard disk and POE): ≤ 10 W

Working Temperature: -10 oC ~ +55 oC (+14 oF~ + 131 oF)

Working Humidity: 10 % ~ 90 %

Chassis: 1U chassis

Dimensions: 200 × 205 × 48 mm
(7.9" × 8.1" × 1.9")

Weight(without HDD): ≤ 1 kg (2.2 lb)

Partners

Partner Tecnologici
Distributori
Embedded Open Platform

Support

Avvisi
Download
White Papers
Centro di sicurezza
Gestione Distributori
Cookie Policy
Privacy Policy

Altro

Richiesta informazioni
Contattaci
Iscrizione alla Newsletter

