



## Info generali

### Tecnico - Proiettori e Binari

Indoor track mounted adjustable projector with integrated LED sources and direct light emission

|               |                              |
|---------------|------------------------------|
| Ean           | 8021696189611                |
| Articolo      | SMILE 15W CRI80 24° 4000K WH |
| Installazione | Proiettori e Binari          |
| Garanzia      | 5 years                      |
| Peso lordo    | 0.61 kg                      |
| Volume        | 0.005011 m <sup>3</sup>      |

## Info tecniche e installative

|                         |                                                                                                      |
|-------------------------|------------------------------------------------------------------------------------------------------|
| Peso netto              | 0.61 kg                                                                                              |
| Classe di isolamento    | II                                                                                                   |
| Grado di protezione     | IP20                                                                                                 |
| Conformità              | CE                                                                                                   |
| Temperatura d'esercizio | 0° ~ +40 °C                                                                                          |
| Dimmer                  | NO, On-Off                                                                                           |
| Alimentazione           | 220-240 V AC 50/60 Hz                                                                                |
| Alimentatore            | In-built, included<br>Replaceable (by qualified operators only),<br>electronic, tridonic             |
| Resistenza al carico    | IK06                                                                                                 |
| Orientabilità           | vert. 0°-90° , orizz. 0°-350°                                                                        |
| Accessori non inclusi   | Honeycomb or Elliptical filter, White decorative ring, Single connection on-off, Link on-off profile |

## Info sorgente e prestazionali

|                       |                                           |
|-----------------------|-------------------------------------------|
| Sorgente integrata    | Integrated LED module                     |
| Sorgente sostituibile | Replaceable (by qualified operators only) |
| Potenza               | 15 W                                      |
| Emissione             | Direct                                    |
| Consumo massimo       | max 15,00 W                               |
| Caratteristiche LED   | LED COB PHILIPS                           |
| CCT LED               | 4000 K                                    |
| Durata LED (t. 25°c)  | 50000 h                                   |
| CRI                   | > 80                                      |
| Fascio luminoso       | 24°                                       |
| Flusso sorgente       | 2250 lm                                   |
| Flusso utile          | 1900 lm                                   |