



Info generali

Tecnico - Proiettori e Binari

Indoor track mounted adjustable projector with integrated LED sources and direct light emission

Ean	8021696189970
Articolo	SMILE 15W CRI90 50° 3000K WH
Installazione	Proiettori e Binari
Garanzia	5 years
Peso lordo	0.61 kg
Volume	0.005011 m ³

Info tecniche e installative

Peso netto	0.61 kg
Classe di isolamento	II
Grado di protezione	IP20
Conformità	CE
Temperatura d'esercizio	0° ~ +40 °C
Dimmer	NO, On-Off
Alimentazione	220-240 V AC 50/60 Hz
Alimentatore	In-built, included Replaceable (by qualified operators only), electronic, tridonic
Resistenza al carico	IK06
Orientabilità	vert. 0°-90° , orizz. 0°-350°
Accessori non inclusi	Honeycomb or Elliptical filter, White decorative ring, Single connection on-off, Link on-off profile

Info sorgente e prestazionali

Sorgente integrata	Integrated LED module
Sorgente sostituibile	Replaceable (by qualified operators only)
Potenza	15 W
Emissione	Direct
Consumo massimo	max 15,00 W
Caratteristiche LED	LED COB PHILIPS
CCT LED	3000 K
Durata LED (t. 25°c)	50000 h
CRI	> 90
Fascio luminoso	50°
Flusso sorgente	1700 lm
Flusso utile	1410 lm