



## Info generali

### Interno - Lampade da parete

Indoor wall mounted lamp with multiple integrated LED sources, in-built switch, in-built USB port and diffuse light emission

|               |                         |
|---------------|-------------------------|
| Ean           | 8021696239521           |
| Articolo      | GEA MAP2 BIANCO         |
| Installazione | Lampade da parete       |
| Garanzia      | 5 years                 |
| Peso lordo    | 0.65 kg                 |
| Volume        | 0.002184 m <sup>3</sup> |

## Info tecniche e installative

|                         |                                                                                |
|-------------------------|--------------------------------------------------------------------------------|
| Peso netto              | 0.5 kg                                                                         |
| Classe di isolamento    | I                                                                              |
| Grado di protezione     | IP20                                                                           |
| Conformità              | CE                                                                             |
| Temperatura d'esercizio | 0° ~ +40 °C                                                                    |
| Dimmer                  | NO, On-Off                                                                     |
| Alimentazione           | 220-240 V AC 50/60 Hz<br>Integrated switch button Integrated USB socket        |
| Alimentatore            | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

## Info sorgente e prestazionali

|                       |                                                |
|-----------------------|------------------------------------------------|
| Sorgente integrata    | Integrated LED module                          |
| Sorgente sostituibile | Replaceable (LED: by qualified operators only) |
| Potenza               | 3 W                                            |
| Emissione             | Diffuse                                        |
| Consumo massimo       | max LED 3.0 W                                  |
| Caratteristiche LED   | LED SMD                                        |
| CCT LED               | 3000 K                                         |
| Durata LED (t. 25°C)  | 20000 h                                        |
| CRI                   | > 80                                           |
| Fascio luminoso       | -                                              |
| Flusso sorgente       | 200 lm                                         |
| Flusso utile          | LED 130 lm                                     |
| Rischio fotobiologico | 2                                              |