



Info generali

Interno - Lampade da soffitto

Indoor ceiling or wall mounted lamp with integrated LED sources, in-built switch with settable CCT and direct light emission

Ean	8021696327693
Articolo	RAY PL D60 BIANCO
Installazione	Lampade da soffitto
Garanzia	5 years
Peso lordo	3.57 kg
Volume	0.035154 m ³

Info tecniche e installative

Peso netto	3.24 kg
Classe di isolamento	II
Grado di protezione	IP44
Conformità	CE
Temperatura d'esercizio	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off, CCT Switch on Board
Alimentazione	220-240 V AC 50/60 Hz
Alimentatore	In-built, included Replaceable (by qualified operators only), electronic

Info sorgente e prestazionali

Sorgente integrata	Integrated LED module
Sorgente sostituibile	Replaceable (by qualified operators only)
Potenza	44 W
Emissione	Direct
Consumo massimo	max 44 W
Caratteristiche LED	LED SMD
CCT LED	3000-4000 K
Durata LED (t. 25°C)	50000 h
CRI	> 90
SDCM	3
Fascio luminoso	77°
UGR massimo	< 19
Flusso sorgente	7200 lm
Flusso utile	5170-5460 lm
Rischio fotobiologico	1