



Info generali

Interno - Applique

Indoor wall mounted adjustable and dimmable lamp with integrated LED sources, in-built switch, in-built integrated battery and direct light emission

Ean	8021696364810
Articolo	BEAN AP ROUND RECHARGEABLE NICKEL
Installazione	Applique
Garanzia	5 years
Peso lordo	0.32 kg
Volume	0.00119 m ³

Info tecniche e installative

Peso netto	0.31 kg
Classe di isolamento	III
Grado di protezione	IP20
Conformità	CE
Temperatura d'esercizio	0° ~ +40 °C
Dimmer	1, Touch dimmer
Alimentazione	5 V DC 50/60 Hz
Alimentatore	Required, separate, not included (power charger, output 5 V DC 2 A USB-C type) electronic

Info sorgente e prestazionali

Sorgente integrata	Integrated LED module
Sorgente sostituibile	No
Potenza	LED 3 W
Emissione	Direct
Consumo massimo	max 3 W
Caratteristiche LED	LED SMD BRIDGELUX
CCT LED	3000 K
Durata LED (t. 25°C)	50000 h
CRI	> 95
SDCM	3
Fascio luminoso	27°
Flusso sorgente	200 lm
Flusso utile	180 lm
Rischio fotobiologico	2
Potenza in stand-by	< 0.50 W