



Numero di lampade per vano: 1
 Attacco: /
 Perdite del trasformatore [W]: 4.3
 Temperatura colore [K]: 3000
 IRC: 80
 Lunghezza d'onda [nm]: /
 Step MacAdam: 3

--

R	77	75	73	71	55	53	33	00	DRR
K0.8	74	70	67	65	69	66	66	63	77
1.0	77	73	71	69	72	70	70	67	82
1.5	81	78	76	74	77	75	75	72	88
2.0	83	81	80	78	80	79	78	76	92
2.5	85	83	82	81	82	81	80	78	95
3.0	86	85	84	83	84	83	82	80	97
4.0	87	86	86	85	85	84	83	81	99
5.0	87	87	86	86	86	85	84	82	100

QC	A	G	1.15	2000	1000	500	<~300		
	B		1.50		2000	1000	750	500	<~300
	C		1.85			2000		1000	500
85°									
75°									
65°									
55°									
45°									
C0-180									

Corrected UGR values (at 5000 lm bare lamp luminous flux)											
Reflect.: ceiling walls work pl. Room dim x y		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
viewed crosswise						viewed endwise					
2H	2H	16.9	17.5	17.1	17.7	17.9	16.9	17.5	17.1	17.7	17.9
	3H	16.7	17.3	17.0	17.6	17.8	16.7	17.3	17.0	17.5	17.8
	4H	16.7	17.2	17.0	17.5	17.8	16.7	17.2	17.0	17.5	17.8
	6H	16.6	17.1	16.9	17.4	17.7	16.6	17.1	16.9	17.4	17.7
	8H	16.6	17.0	16.9	17.3	17.7	16.5	17.0	16.9	17.3	17.7
	12H	16.5	17.0	16.9	17.3	17.6	16.5	16.9	16.9	17.3	17.6
4H	2H	16.7	17.2	17.0	17.5	17.8	16.7	17.2	17.0	17.5	17.8
	3H	16.5	17.0	16.9	17.3	17.6	16.5	17.0	16.9	17.3	17.6
	4H	16.4	16.8	16.8	17.2	17.6	16.4	16.8	16.8	17.2	17.6
	6H	16.4	16.7	16.8	17.1	17.5	16.4	16.7	16.8	17.1	17.5
	8H	16.3	16.6	16.8	17.0	17.5	16.3	16.6	16.7	17.0	17.5
	12H	16.3	16.5	16.7	17.0	17.4	16.3	16.5	16.7	17.0	17.4
8H	4H	16.3	16.6	16.7	17.0	17.5	16.3	16.6	16.8	17.0	17.5
	6H	16.2	16.5	16.7	16.9	17.4	16.2	16.5	16.7	16.9	17.4
	8H	16.2	16.4	16.7	16.9	17.4	16.2	16.4	16.7	16.9	17.4
	12H	16.1	16.3	16.6	16.8	17.3	16.1	16.3	16.6	16.8	17.3
12H	4H	16.3	16.5	16.7	17.0	17.4	16.3	16.5	16.7	17.0	17.4
	6H	16.2	16.4	16.7	16.9	17.4	16.2	16.4	16.7	16.9	17.4
	8H	16.1	16.3	16.6	16.8	17.3	16.1	16.3	16.6	16.8	17.3

Variations with the observer position at spacing:		
S =	1.0H	5.7 / -12.0
	1.5H	8.5 / -13.0
	2.0H	10.5 / -14.4