



$I_{\max}=1410 \text{ cd}$ $\alpha = 78^\circ$ 1500 0°	CIE nL 0.75 73-90-98-100-75 UGR 26.8-26.4		Lux			
	DIN A.51					
	UTE 0.75B+0.00T F*1=728 F*1+F*2=904 F*1+F*2+F*3=981					
	CIBSE BZ2-4/BZ3					
			h	d	Em	Emax
			1	1.6	977	1410
			2	3.2	244	352
			3	4.9	109	157
			4	6.5	61	88

Coefficienti di utilizzazione

R	77	75	73	71	55	53	33	00	DRR
K0.8	58	52	48	45	52	48	47	44	58
1.0	62	57	53	50	56	52	52	48	64
1.5	68	64	61	58	63	60	59	55	74
2.0	72	68	66	63	67	65	64	60	81
2.5	74	71	69	67	70	68	67	64	85
3.0	75	73	71	69	71	70	69	66	88
4.0	77	75	74	72	73	72	71	68	91
5.0	78	76	75	74	75	74	72	70	93

Diagramma UGR

Corrected UGR values (at 3000 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
		viewed crosswise					viewed endwise				
2H	2H	24.1	25.0	24.4	25.3	25.5	24.1	25.0	24.4	25.3	25.5
	3H	25.1	25.9	25.4	26.2	26.5	24.4	25.2	24.7	25.5	25.8
	4H	25.5	26.3	25.8	26.6	26.9	24.4	25.2	24.8	25.5	25.9
	6H	25.8	26.5	26.2	26.9	27.2	24.5	25.2	24.8	25.5	25.9
	8H	25.9	26.6	26.3	26.9	27.3	24.5	25.2	24.8	25.5	25.9
	12H	26.0	26.6	26.3	27.0	27.3	24.4	25.1	24.8	25.5	25.8
4H	2H	24.4	25.2	24.8	25.5	25.9	25.5	26.3	25.8	26.6	26.9
	3H	25.7	26.3	26.1	26.7	27.0	26.0	26.7	26.4	27.0	27.4
	4H	26.2	26.8	26.6	27.2	27.6	26.2	26.8	26.6	27.2	27.6
	6H	26.7	27.2	27.1	27.6	28.0	26.4	26.9	26.8	27.3	27.7
	8H	26.8	27.3	27.2	27.7	28.1	26.4	26.9	26.9	27.3	27.8
	12H	26.9	27.3	27.3	27.7	28.2	26.4	26.8	26.9	27.3	27.7
8H	4H	26.4	26.9	26.9	27.3	27.8	26.8	27.3	27.2	27.7	28.1
	6H	27.0	27.4	27.4	27.8	28.3	27.1	27.5	27.5	27.9	28.4
	8H	27.2	27.5	27.7	28.0	28.5	27.2	27.5	27.7	28.0	28.5
	12H	27.3	27.6	27.8	28.1	28.6	27.2	27.5	27.7	28.0	28.5
12H	4H	26.4	26.8	26.9	27.3	27.7	26.9	27.3	27.3	27.7	28.2
	6H	27.0	27.3	27.5	27.8	28.3	27.2	27.5	27.7	28.0	28.5
	8H	27.2	27.5	27.7	28.0	28.5	27.3	27.6	27.8	28.1	28.6
Variations with the observer position at spacing:											
S =		1.0H	0.7 / -0.5		0.7 / -0.5						
		1.5H	1.3 / -0.8		1.3 / -0.8						
		2.0H	2.3 / -1.0		2.3 / -1.0						