

Codice articolo



CHIN 06 L






Custodia da incasso, serie LS-TYPE, con 1 leva, grandezza "44.27"

Descrizione prodotto		Proprietà dei materiali	
Tipo prodotto	Custodia da incasso	Altri materiali	Leva: Poliammide (PA) Guarnizione: NBR
Serie	LS-TYPE	Colore	Nero RAL 9005
Tipo chiusura	Con 1 leva	Conformità RoHs	Conforme
Grandezza	Grandezza "44.27"	China RoHs - EFUP	E
Ingresso cavo	Senza ingresso cavo	Sostanze REACH SVHC	No
Dati tecnici		Approvazioni / Normative	
Grado di protezione IP	IP65	Certificazioni	DNV, BV
Ulteriori dettagli tecnici		UL	ECBT2
Peso	65,00 g	cUL	ECBT8
Temperature di esercizio (min, max)	-40°C...+125°C	Informazioni commerciali	
		Codice EAN13	8015747161596
		Classificazione ecl@ss	27440202
		Classificazione ETIM	EC000437
Caratteristiche imballaggio			
		Lunghezza imballo	255,00 mm
		Altezza imballo	195,00 mm
		Profondità imballo	245,00 mm
		Peso imballo	2,60 kg
		Volume imballo	12,18 dm³
		Descrizione imballo	Scatola cartone
		Quantità imballo	40 pz
		Codice EAN13 imballo	8015747187565
		Peso sottoimballo	0,33 kg
		Descrizione sottoimballo	Termoretraibile
		Quantità sottoimballo	5 pz
		Codice EAN13 sottoimballo	8015747187572

CHIN 06 L



Disegni da catalogo

CH..N - MA, MF..N enclosures		size "44.27"	LS-TYPE version
inserts: page CDD 24 poles + @ 59 * CQE 10 poles + @ 80 * CSH 6 poles + @ 88 * CCE 6 poles + @ 94 * CNE, CSE, JCNE, JCSE 6 poles + @ 95 and 105 * CSS 6 poles + @ 118 * CTE, CTSE **) 6 poles + @ 126 * MIXO 2 modules 160x195 * insert centre distance: 44 x 27 mm * refer to catalogue page CN.12		housings with single lever 	hoods with 2 pegs 
description	part no. entry M	part no. entry M	
bulkhead mounting housing, with lever	CHIN 06 L		
surface mounting housing, high construction, with lever	MAPN 06 L32 32		
with pegs, side entry		MHON 06 L25 25	
with pegs, side entry, high construction		MFON 06 L25 25	
with pegs, top entry		MHVN 06 L25 25	
with pegs, top entry, high construction		MFVN 06 L25 25	
**) only in the CHIN 06 L enclosure			
panel cut-out for bulkhead mounting housing in mm	dimensions in mm CHIN 06 L  MAPN 06 L32 	dimensions in mm MFON 06 L25  MFVN 06 L25  MHON 06 L25  MHVN 06 L25 	
- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)			
 dimensions shown are not binding and may be changed without notice			

4

Note

Le misure indicate non sono impegnative e possono essere variate senza alcun preavviso.