

Codice articolo

CHIN 16



Custodia da incasso, serie LS-TYPE, con 2 leve, grandezza "77.27"

Descrizione prodotto

Tipo prodotto	Custodia da incasso
Serie	LS-TYPE
Tipo chiusura	Con 2 leve
Grandezza	Grandezza "77.27"
Ingresso cavo	Senza ingresso cavo

Dati tecnici

Grado di protezione IP	IP65
-------------------------------	------

Ulteriori dettagli tecnici

Peso	95,00 g
Temperature di esercizio (min, max)	-40°C...+125°C

Proprietà dei materiali

Altri materiali	Leva: Poliammide (PA) Guarnizione: NBR
Colore	Nero RAL 9005
Conformità RoHs	Conforme
China RoHs - EFUP	E
Sostanze REACH SVHC	No

Approvazioni / Normative

Certificazioni	DNV, BV
UL	ECBT2
cUL	ECBT8

Informazioni commerciali

Codice EAN13	8015747163095
Classificazione ecl@ss	27440202
Classificazione ETIM	EC000437


Caratteristiche imballaggio

Lunghezza imballo	360,00 mm
Altezza imballo	165,00 mm
Profondità imballo	315,00 mm
Peso imballo	3,80 kg
Volume imballo	18,71 dm ³
Descrizione imballo	Scatola cartone
Quantità imballo	40 pz
Codice EAN13 imballo	8015747187602
Peso sottoimballo	0,48 kg
Descrizione sottoimballo	Termoretraibile
Quantità sottoimballo	5 pz
Codice EAN13 sottoimballo	8015747187619

Codice articolo CHIN 16



Disegni da catalogo



Disegni da catalogo

CH..N - MA, MF..N enclosures size "77.27" LS-TYPE version

inserts:	page	housings with double lever	hoods with 4 pegs
CD	40 poles + @ 49+52 *		
CT, CTS **)	40 poles + @ 56 *		
CDD	72 poles + @ 62+65 *		
CDE	32 poles + @ 82+84 *		
CSH	16 poles + @ 90+92 *		
CCE	16 poles + @ 98+102 *		
CNE, CSE, JCNE, JCSE	16 poles + @ 99 and 108 *		
CSS	16 poles + @ 120+122 *		
CTE, CTSE **)	16 poles + @ 128 *		
CMSE	6+2 (aux) poles + @ 137 *		
CMCE	6+2 (aux) poles + @ 136 *		
CP	6 poles + @ 149+150 *		
CX	6/36 e 12/2 poles + @ 152+153 *		
CX	4/0 e 4/2 poles + @ 154 *		
MIXO	4 modules 160-195 *		

insert centre distance: 77,5 x 27 mm
* refer to catalogue page CN.12

description	part no.	entry	part no.	entry
bulkhead mounting housing, with 2 levers	CHIN 16	M		
surface mounting housing, high construction, with 2 levers	MAPN 16.32	32		
with pegs, side entry			MHON 16.32	32
with pegs, side entry, high construction			MFON 16.32	32
with pegs, top entry			MHVN 16.32	32
with pegs, top entry, high construction			MFVN 16.32	32

**) only in the CHIN 16 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

dimensions in mm	dimensions in mm
CHIN 16	MFON 16.32
MAPN 16.32	MFVN 16.32
	MHON 16.32
	MHVN 16.32

8

Note

Le misure indicate non sono impegnative e possono essere variate senza alcun preavviso.