

Codice articolo

# CHIN 24



Custodia da incasso, serie LS-TYPE, con 2 leve, grandezza "104.27"

#### Descrizione prodotto

<b>Tipo prodotto</b>	Custodia da incasso
<b>Serie</b>	LS-TYPE
<b>Tipo chiusura</b>	Con 2 leve
<b>Grandezza</b>	Grandezza 104.27
<b>Ingresso cavo</b>	Senza ingresso cavo

#### Dati tecnici

<b>Grado di protezione IP</b>	IP65
-------------------------------	------

#### Ulteriori dettagli tecnici

<b>Peso</b>	98,00 g
<b>Temperature di esercizio (min, max)</b>	-40°C...+125°C

#### Proprietà dei materiali

<b>Altri materiali</b>	Leva: Poliammide (PA) Guarnizione: NBR
<b>Colore</b>	Nero RAL 9005
<b>Conformità RoHs</b>	Conforme
<b>China RoHs - EFUP</b>	E
<b>Sostanze REACH SVHC</b>	No

#### Approvazioni / Normative

<b>Certificazioni</b>	DNV, BV
<b>UL</b>	ECBT2
<b>cUL</b>	ECBT8

#### Informazioni commerciali

<b>Codice EAN13</b>	8015747163101
<b>Classificazione ecl@ss</b>	27440202
<b>Classificazione ETIM</b>	EC000437


#### Caratteristiche imballaggio

<b>Lunghezza imballo</b>	250,00 mm
<b>Altezza imballo</b>	145,00 mm
<b>Profondità imballo</b>	300,00 mm
<b>Peso imballo</b>	1,96 kg
<b>Volume imballo</b>	10,88 dm <sup>3</sup>
<b>Descrizione imballo</b>	Scatola cartone
<b>Quantità imballo</b>	20 pz
<b>Codice EAN13 imballo</b>	8015747187626
<b>Peso sottoimballo</b>	0,49 kg
<b>Descrizione sottoimballo</b>	Termoretraibile
<b>Quantità sottoimballo</b>	5 pz
<b>Codice EAN13 sottoimballo</b>	8015747187633

# Codice articolo CHIN 24



Disegni da catalogo



Disegni da catalogo

**CH..N - MA, MF..N enclosures** size "104.27" **LS-TYPE version**

inserts:	page	housings with double lever	hoods with 4 pegs
CD .....	64 poles + @ 51+53 *		
CT, CTS **) .....	64 poles + @ 57 *		
CDD .....	108 poles + @ 64+66 *		
CDE .....	46 poles + @ 83+85 *		
CSH .....	24 poles + @ 91+93 *		
CCE .....	24 poles + @ 100+104 *		
CNE, CSE, JCNE, JCSE .....	24 poles + @ 101 and 109 *		
CSS .....	24 poles + @ 122+123 *		
CTE, CTSE **) .....	24 poles + @ 129 *		
CMSE .....	10+2 (aux) poles + @ 139 *		
CMCE .....	10+2 (aux) poles + @ 138 *		
CX .....	4/8 poles + @ 155 *		
MIXO .....	6 modules 160+195 *		

insert centre distance: 104 x 27 mm  
\* refer to catalogue page CN.12

description	part no.	entry	part no.	entry
bulkhead mounting housing, with 2 levers	<b>CHIN 24</b>	M		
surface mounting housing, high construction, with 2 levers	<b>MAPN 24.32</b>	<b>32</b>		
with pegs, side entry			<b>MHON 24.32</b>	<b>32</b>
with pegs, side entry, high construction			<b>MFON 24.32</b>	<b>32</b>
with pegs, side entry			<b>MHVN 24.32</b>	<b>32</b>
with pegs, side entry, high construction			<b>MFVN 24.32</b>	<b>32</b>

\*\*) only in the CHIN 24 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder  
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

dimensions in mm

**CHIN 24**

**MAPN 24.32**

dimensions in mm

**MFON 24.32**

**MFVN 24.32**

**MHON 24.32**

**MHVN 24.32**

## Note

Le misure indicate non sono impegnative e possono essere variate senza alcun preavviso.