

Codice articolo

MFON 16.32



Custodia mobile, serie LS-TYPE, con 4 piolini, ingresso cavo orizzontale M32 senza adattatore, grandezza "77.27", alta


Descrizione prodotto		Proprietà dei materiali	
Tipo prodotto	Custodia mobile	Colore	Nero RAL 9005
Serie	LS-TYPE	Conformità RoHs	Conforme
Tipo chiusura	Con 4 piolini	China RoHs - EFUP	E
Grandezza	Grandezza "77.27"	Sostanze REACH SVHC	No
Ingresso cavo	Ingresso cavo orizzontale M32	Approvazioni / Normative	
Specifica	Alta	Certificazioni	DNV, BV
Dati tecnici		UL	ECBT2
Grado di protezione IP	IP65	cUL	ECBT8
Ulteriori dettagli tecnici		Informazioni commerciali	
Peso	258,00 g	Codice EAN13	8015747044295
Temperature di esercizio (min, max)	-40°C...+125°C	Classificazione ecl@ss	27440202
		Classificazione ETIM	EC000437
Caratteristiche imballaggio			
Lunghezza imballo	190,00 mm		
Altezza imballo	140,00 mm		
Profondità imballo	290,00 mm		
Peso imballo	5,26 kg		
Volume imballo	7,71 dm³		
Descrizione imballo	Scatola cartone		
Quantità imballo	20 pz		
Codice EAN13 imballo	8015747187732		
Peso sottoimballo	1,32 kg		
Descrizione sottoimballo	Termoretraibile		
Quantità sottoimballo	5 pz		
Codice EAN13 sottoimballo	8015747187749		

Codice articolo

MFON 16.32



Disegni da catalogo



Disegni da catalogo

CH..N - MA, MF..N enclosures

size "77.27"

LS-TYPE version

inserts:

CD	40 poles + @	49+52 *
CT, CTS **)	40 poles + @	56 *
CDD	72 poles + @	62+65 *
CDE	32 poles + @	82+84 *
CSH	16 poles + @	90+92 *
CCE	16 poles + @	98+102 *
CNE, CSE, JCNE, JCSE	16 poles + @	99 and 108 *
CSS	16 poles + @	120+122 *
CTE, CTSE **)	16 poles + @	128 *
CMSE	6+2 (aux) poles + @	137 *
CMCE	6+2 (aux) poles + @	136 *
CP	6 poles + @	149+150 *
CX	6/36 e 12/2 poles + @	152+153 *
CX	4/0 e 4/2 poles + @	154 *
MIXO	4 modules	160+195 *

insert centre distance: 77,5 x 27 mm

* refer to catalogue page CN.12

description	part no.	entry
bulkhead mounting housing, with 2 levers	CHIN 16	
surface mounting housing, high construction, with 2 levers	MAPN 16.32	32
with pegs, side entry		
with pegs, side entry, high construction		
with pegs, top entry		
with pegs, top entry, high construction		

** only in the CHIN 16 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder

- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

housings with double lever

hoods with 4 pegs

part no.

entry

M

part no.

entry

M

dimensions in mm

CHIN 16

dimensions in mm

MFON 16.32

dimensions in mm

MAPN 16.32

dimensions in mm

MFVN 16.32

dimensions in mm

MHON 16.32

dimensions in mm

MHVN 16.32

Note

Le misure indicate non sono impegnative e possono essere variate senza alcun preavviso.