

Codice articolo

MHVN 06 L25



Custodia mobile, serie LS-TYPE, con 2 piolini, ingresso cavo verticale M25, grandezza "44.27"


Descrizione prodotto		Proprietà dei materiali	
Tipo prodotto	Custodia mobile	Colore	Nero RAL 9005
Serie	LS-TYPE	Conformità RoHs	Conforme
Tipo chiusura	Con 2 piolini	China RoHs - EFUP	E
Grandezza	Grandezza "44.27"	Sostanze REACH SVHC	No
Ingresso cavo	Ingresso cavo verticale M25	Approvazioni / Normative	
Dati tecnici		Certificazioni	DNV, BV
Grado di protezione IP	IP65	UL	ECBT2
Ulteriori dettagli tecnici		cUL	ECBT8
Peso	84,00 g	Informazioni commerciali	
Temperature di esercizio (min, max)	-40°C...+125°C	Codice EAN13	8015747194204
		Classificazione ecl@ss	27440202
		Classificazione ETIM	EC000437
Caratteristiche imballaggio			
		Peso sottoimballo	0,42 kg
		Descrizione sottoimballo	Termoretraibile
		Quantità sottoimballo	5 pz
		Codice EAN13 sottoimballo	8015747123341

Codice articolo

MHVN 06 L25



Disegni da catalogo



Disegni da catalogo

CH..N - MA, MF..N enclosures

size "44.27"

LS-TYPE version

inserts:

CDD	24 poles + Ⓢ	59 *
CQE	10 poles + Ⓢ	80 *
CSH	6 poles + Ⓢ	88 *
CCE	6 poles + Ⓢ	94 *
CNE, CSE, JONE, JCSE	6 poles + Ⓢ 95 and 106 *	118 *
CSS	6 poles + Ⓢ	126 *
CTE, CTSE **)	6 poles + Ⓢ	126 *
MIXO	2 modules	160+195 *

insert centre distance: 44 x 27 mm

* refer to catalogue page CN.12

housings with single lever

hoods with 2 pegs

description	part no.	entry	part no.	entry
bulkhead mounting housing, with lever	CHIN 06 L	M		
surface mounting housing, high construction, with lever	MAPN 06 L32	32		
with pegs, side entry			MHON 06 L25	25
with pegs, side entry, high construction			MFON 06 L25	25
with pegs, top entry			MHVN 06 L25	25
with pegs, top entry, high construction			MFVN 06 L25	25

** only in the CHIN 06 L enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder

- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

IP65

IP65

dimensions shown are not binding and may be changed without notice

dimensions in mm

CHIN 06 L

MAPN 06 L32

dimensions in mm

MFON 06 L25

MFVN 06 L25

MHON 06 L25

MHVN 06 L25

Note

Le misure indicate non sono impegnative e possono essere variate senza alcun preavviso.